Ultranarrow resonance peaks in the transmission and reflection spectra of a photonic crystal cavity with Raman gain

V. G. Arkhipkin^{*} and S. A. Myslivets

L.V. Kirensky Institute of Physics and Siberian Federal University, Krasnoyarsk, Russia (Received 24 August 2009; published 7 December 2009)

The Raman gain of a probe light in a three-state Λ scheme placed into a defect of a one-dimensional photonic crystal is studied theoretically. We show that there exists a pump intensity range, where the transmission and reflection spectra of the probe field exhibit *simultaneously* occurring narrow peaks (resonances) whose position is determined by the Raman resonance. Transmission and reflection coefficients can be larger than unity at pump intensities on the order of tens of μ W/cm². When the pump intensity is outside this region, the peak in the transmission spectrum turns into a narrow dip. The nature of narrow resonances is attributed to a drastic dispersion of the nonlinear refractive index in the vicinity of the Raman transition, which leads to a significant reduction in the group velocity of the probe wave.

DOI: 10.1103/PhysRevA.80.061802

Microdefects and nanodefects in photonic crystals (PCs) are capable of localizing light within a volume smaller than λ^3 (λ being the wavelength) with a high quality factor of defect modes (see [1,2] and references therein). Such structures are often referred to as photonic crystal cavities or microcavities and nanocavities [3]. They find an important application in many different fields such as photonics [4], nonlinear optics [1], quantum electrodynamics [5], and others. These structures also underlie the design of lowthreshold microlasers and nanolasers [6] and Raman lasers [7,8]. Inserting a resonant medium (atoms or quantum wells) into a defect results in a significant modification of spectral properties of the PC [9-11]. Even more intriguing effects can arise from combining PC properties with the properties of electromagnetically induced transparency (EIT) [12]. It has been shown recently that in a PC with a defect containing a EIT material [13], the defect mode Q factor for the probe radiation noticeably increases under EIT [14,15], whereas the width of the transmission spectrum narrows. The increase factor can be of order $c/v_{q} \ge 1$ as under EIT it is quite possible that $v_g \ll c$ [14] (c is the light velocity in vacuum and v_g is the group velocity of a probe wave in a EIT medium). A noticeable reduction in the group velocity (slow light) occurs as well under conventional Raman interaction of a probe (Raman) radiation with a strong pump (driving field) [16-19], and it occurs with a smaller loss and over a broader spectral range than under EIT [16].

In this Rapid Communication we suggest an approach to reduce the width of the transmission (reflection) spectrum of a PC. Our technique is based on the effect of Raman gain [20,21] of a probe wave in a defect layer containing a three-level medium (Fig. 1). A probe (Raman) wave with frequency ω_2 undergoes amplification when interacting with a coherent pump (driving) wave with frequency ω_1 as the difference between the two frequencies comes close to the Raman transition frequency $\omega_{20}=\omega_1-\omega_2$. The pump intensity is chosen so as to ensure the enhancement of the probe wave without however exceeding the stimulated Raman scattering (SRS) threshold. Here, unlike spontaneous Raman scattering,

PACS number(s): 42.70.Qs, 42.50.Gy, 42.55.Sa, 42.65.Dr

phasing of atomic oscillations occurs throughout the entire volume occupied by light waves, just as it happens under SRS, but without uncontrollable instabilities and with the spectral resolution being determined by the spectral width of the applied laser radiation. This scheme is weakly sensitive to pump field intensity fluctuations [21]. We note that Raman gain is being extensively used in high-resolution Raman spectroscopy in gases and liquids [21] as well as in designing high-efficiency continuous-wave Raman amplifiers and lasers [22,23].

Consider a one-dimensional photonic crystal having a $(HL)^M HDH(LH)^M$ -type structure. Here, H and L refer to different dielectric layers with high and low refractive indices, n_H and n_L , and thicknesses t_H and t_L , respectively; D is the defect layer with a t_D thickness and the refractive index n_D ; and M is the number of periods. The defect layer is filled with three-level atoms. Figure 1 shows the energy-level diagram and relevant laser couplings for the present study. The concentration of atoms is such that we can assume that there is no interaction between atoms. Parameters of the PC are chosen to allow excitation of just one defect mode whose spectral width is much larger than that of the allowed transitions and of the Raman transition $|0\rangle - |2\rangle$ (in contrast to [7,8] and references therein).

Two monochromatic plane waves (the pump and probe) with $\omega_{1,2}$ are normally incident on the PC and propagate along the *z* axis (*z*=0 at the first layer boundary), which is



FIG. 1. Energy-level diagram of a three-level atom in a Raman gain scheme. States 0 and 2 are the ground and metastable states, respectively.

^{*}avg@iph.krasn.ru

^{1050-2947/2009/80(6)/061802(4)}

perpendicular to the PC layers. The frequency difference $\omega_1 - \omega_2$ is close to the Raman transition frequency ω_{20} . The pump field E_1 interacts with the $|0\rangle - |1\rangle$ transition and the probe field E_2 interacts with the adjacent transition $|1\rangle - |2\rangle$. The $|0\rangle - |2\rangle$ transition is dipole forbidden. Only the lower ground state $|0\rangle$ is initially populated. Both waves are assumed to fall within the transmission band of the photonic crystal, i.e., the transition frequency ω_{20} is less than the defect mode width. For simplicity, a unity refractive index is assumed for the medium containing the photonic crystal.

For rarefied medium the complex refractive index of the defect layer $n_D = n_2$ for a probe field in the presence of a pump wave is given by [24]

$$n_2 = n'_2 + in''_2 = \sqrt{1 + 4\pi N(\chi_2^{(1)} + \chi_R |E_1|^2)}$$

$$\approx 1 + 2\pi N(\chi_2^{(1)} + \chi_R |E_1|^2),$$

where $\chi_2^{(1)}$ is the linear nonresonant susceptibility for the probe field, E_1 is the complex amplitude of the pump wave, N is the concentration of atoms, and χ_R is the Raman susceptibility [25]

$$\chi_{R} = \frac{1}{4\hbar^{3}} \frac{d_{21}^{2} d_{10}^{2}}{(\omega_{10} - \omega_{1})^{2} [\omega_{20} - (\omega_{1} - \omega_{2}) + i\gamma_{20}]}$$

Here, ω_{10} and ω_{20} are the frequencies of atomic transitions, γ_{20} is the $|0\rangle - |2\rangle$ Raman transition half width, d_{ij} is the matrix dipole moment of the transition, and \hbar is the Planck constant.

The formula for χ_R was obtained in the third order of perturbation theory under the following conditions: Ω_1 = $|\omega_{10}-\omega_1| \ge |G_1|, |G_2|, \gamma_{10}$ and $|G_1| \ge |G_2|$, where $2G_1$ and $2G_2$ are Rabi frequencies of the pump and the probe waves, respectively, and γ_{10} is the half width of the $|0\rangle - |1\rangle$ transition. Population of the lower state $|0\rangle$ can be considered unaffected under these conditions. For simplicity, we neglect the Doppler broadenings because the one-photon detuning Ω_1 is sufficiently large and the residual Doppler broadening of Raman transition is small.

Note that, in the given approximation, $|\text{Im }\chi_R| \ge |\text{Im }\chi_2^{(1)}|$, and the only effect of Re $\chi_2^{(1)}$ is to shift the resonant frequency of the defect mode. Therefore, the contribution of $\chi_2^{(1)}$ into the refractive index n_2 will be neglected in our further consideration. It is essential that the imaginary part of χ_R is negative in the vicinity of the Raman resonance, which implies the probe wave enhancement due to energy transfer from the pump to the probe field. The real part of the refractive index n'_2 =Re n_2 has normal dispersion $(dn'_2/d\omega_2>0)$ [26] in this region; therefore, the group velocity of the probe wave can be smaller than the light velocity in vacuum [16].

In a steady-state approximation, a field in an arbitrary *j*th layer (j=H,L,D) can be treated as a superposition of counterpropagating waves,

$$E_{i} = A_{i} \exp[ik_{i}(z - z_{i})] + B_{i} \exp[-ik_{i}(z - z_{i})],$$

where A_j and B_j are amplitudes of the forward (incident) and backward (reflected) waves and $k_j = n_j \omega_{1,2}/c$, where n_j is the refractive index of a *j*th layer. Note that the refractive index of a defect layer for the probe wave n'_2 depends on the spatial

PHYSICAL REVIEW A 80, 061802(R) (2009)



FIG. 2. (Color online) (a) Transmission *T* and (b) reflection *R* spectra of the photonic crystal cavity for the probe light vs the probe field detuning $\Omega_2 = (\omega_{12} - \omega_2)$ scaled to γ_{10} for various values of a Rabi frequency of the pump field G_1 . Insets: the large-scaled (a) transmission and (b) reflection spectra.

coordinate z since the distribution of fields in a defect is nonuniform due to the effect of localization.

Amplitudes A_j and B_j for each layer were found from wave equations by means of recurrent relations [15,27] using the continuity of tangential components of the electric and magnetic fields at the interface of adjacent layers. The transmission and reflection spectra were determined as

$$T(\omega) = |A_2(L)|^2 / |A_{02}|^2$$
, $R(\omega) = |B_2(0)|^2 / |A_{02}|^2$,

where A_{02} and $A_2(L)$ are the input (z=0) and output (z=L is the photonic crystal length) amplitudes of the probe wave, respectively, and $B_2(0)$ is the amplitude of the probe wave reflected from the input face of the photonic crystal.

For the purpose of numerical simulation, we used sodium atomic parameters as a Raman medium. Wavelengths of the probe and the pump fields were chosen to be close to D_1 line and ω_{20} was chosen to be 1.8 GHz. The photonic crystal had the following parameters: M=10, $n_H d_H = n_L d_L = \lambda_2/4$, $d_D n_D$ $=\lambda_2/2$, $n_H=2.35$, and $n_L=1.45$. The probe wavelength was chosen so that its frequency under Raman resonance ω_1 $-\omega_2 = \omega_{20}$ would match the defect mode resonance frequency, with the pump detuning being $\Omega_1 = 30\gamma_{10}$, $\gamma_{10} = 2\pi$ $\times 10^8$ s⁻¹, $\gamma_{20}/\gamma_{10}=0.1$, and $N \simeq 10^{12}$ cm⁻³. For the chosen parameters, the calculation of field distribution in the empty defect layer yields a virtually complete spatial overlapping of the pump and the probe fields. Intensities of both fields in the defect layer appear to be 10^5 times as strong as the input ones. Since we assume that in a defect layer $|G_1| \ge |G_2|$, simulation of the transmission and reflection coefficients for the probe field was performed in the undepleted-pump approximation.

Figure 2(a) shows typical PC transmission and reflection spectra calculated for the probe wave at different intensities of the driving field. Narrow structures (a peak or a dip) due to the Raman resonance can be observed in the center on the background of a broad transmission band [Fig. 2(a)]. The transmittance can be larger than unity. A narrow peak is also observed in the center of the dip in the reflection spectrum [Fig. 2(b)] and again the reflectance can be larger than unity. So in a PC with a defect producing the Raman gain, narrow ULTRANARROW RESONANCE PEAKS IN THE ...

peaks are observed simultaneously in both the transmission and the reflection spectra. In Fig. 3 transmittance and reflectance maxima are plotted as functions of the Rabi frequency of the driving field. It is seen that the amplitude of the transmission and reflection peaks enhances with the growing pump intensity until the Rabi frequency reaches a threshold, whose value depends on the system parameters. Once this frequency goes beyond the threshold, the amplitude of the transmission peak decreases and the narrow peak is replaced with a dip while the reflectance tends to unity.

A qualitative interpretation of the features of the transmission and reflection spectra of a probe field becomes possible if we look at the problem in terms of a Fabry-Pérot cavity (FPC) [2] with the length *d* equal to the thickness of the defect layer t_D , which is filled with a Raman medium. The FPC transmittance for a probe wave $T=I_2/I_{20}$ (I_{20} is the light intensity as it enters FPC and I_2 is the transmitted light intensity) can be found from the formula

$$T = \frac{T_M^2 e^{\alpha d}}{(1 - R_M e^{\alpha d})^2 + 4R_M e^{\alpha d} \sin^2(\Phi/2)},$$

where T_M and R_M are the transmission and reflection coefficients of mirrors, $\alpha = -(4\pi/\lambda)n''_{eff} > 0$ is the Raman gain factor of the probe wave, $\Phi = (4\pi/\lambda)n'_{eff}d$ is the phase shift after two passes through the cavity, $n''_{eff} = 2\pi N\chi''_R F|E_1|^2$ and $n'_{eff} = 1 + 2\pi N\chi'_R F|E_1|^2$ are effective imaginary and real parts of the refractive index n_2 , E_1 is the pump field amplitude in FPC, and $F = \int_0^d \sin(k_2 z) \sin^2(k_1 z) dz / \int_0^d \sin^2(k_2 z) dz$ is the spatial overlapping integral of the pumping wave and the probe field [29].

The requirement that $\Phi = 2\pi m$ (m = 1, 2, ...) determines a resonance frequency of the cavity, for which maximum transmission is observed,

$$T_{max} = \frac{T_M^2 e^{\alpha d}}{(1 - R_M e^{\alpha d})^2}.$$
 (1)

For $\alpha d \ll 1$, formula (1) can be rewritten as

$$T_{max} \simeq \frac{T_M^2}{(T_M - \alpha dR_M)^2}.$$
 (2)

From formula (2) it follows that at $\alpha dR_M < T_M$ the transmission coefficient grows with the pump intensity $[(T_M - \alpha dR_M) \rightarrow 0]$ and can become $T_{max} \ge 1$. In an opposite situation, when $\alpha dR_M > T_M$, the transmittance T_{max} decreases as the pump field grows (Fig. 3), and when $\alpha dR_M > 2T_M$ a dip is formed in the transmission curve. A similar approach can be applied to analyze the reflection coefficient.

The width (at half maximum) of the narrow transmission peak is given by the expression

$$\delta\omega = \frac{\Delta\omega}{1+\eta}, \quad \Delta\omega = \frac{c}{d} \frac{|1-R_M e^{\alpha d}|}{e^{\alpha d/2} \sqrt{R_M}} \simeq \frac{c}{d} \frac{|T_M - \alpha dR_M|}{\sqrt{R_M}},$$
(3)

where $\eta = 2\pi NF |E_1|^2 \omega_0 \partial \chi'_R / \partial(\omega_2) = K_{12} |G_1|^2 / \Omega_1^2 \gamma_{20}^2$, ω_0 is the resonance frequency of the empty cavity, and $K_{12} = 2\pi NF \omega_0 |d_{12}|^2 / \hbar$. A frequency derivative is taken at $\omega_2 = \omega_0$. For $\alpha = 0$, the formula for $\Delta \omega$ turns into a familiar

PHYSICAL REVIEW A 80, 061802(R) (2009)



FIG. 3. (Color online) The transmission (*T*) and reflection (*R*) maxima vs the Rabi frequency of the driving field G_1 .

expression for a transmission bandwidth of the empty FPC [28]. Note that, when F=1, the value of $1+\eta$ equals the group velocity index $N_g=c/v_g$ for a probe wave under Raman interaction [16], which can be much larger than unity if the dispersion is high (at a small width of the Raman transition).

It is seen from Eq. (3) that the width of the transmission peak for $\eta \ge 1$ is a factor of η narrower than that of the empty cavity, i.e., there appears a narrow transmission peak. The value of η is determined by Raman susceptibility dispersion and depends on the pump intensity. Analysis reveals that the resonance width can be less than the width of the Raman transition γ_{20} . The intensity required for these effects to be observed depends on a number of factors (one-photon pump frequency detuning, Raman resonance width, and quality factor of defect modes) and can be anything from several to hundreds of $\mu W/cm^2$ and less.

To summarize the above, we have studied theoretically light propagation through a photonic crystal with a defect filled with a Raman gain medium and shown that narrow peaks can arise simultaneously in the transmission and reflection spectra of the probe radiation. The position of resonant peaks is determined by the Raman resonance. Transmission and reflection coefficients can be larger than unity. The nature of narrow resonances is attributed to the dispersion of the nonlinear refractive index near a Raman transition. Narrow-band lasers are required to be able to observe the described effects. We believe that the predicted effects can be also observed in cold atoms, including single atoms placed into a PC defect, similar to EIT in a cavity [30,31]. A combination of the Raman gain effect with the advantages of photonic crystal cavities can be useful for various applications. For example, this could help us to further reduce the group velocity and obtain longer pulse delays thereby facilitating the designing of Raman lasers of a new generation and atomic clock.

This work was supported in part by the Presidium of the RAS (Project No. 27.1), by the Department of Physical Sciences, RAS (Project No. 9.1), and also by Federal Task Program (Contract No. g/c 02.740.11.0220).

- [2] P. Lalanne, C. Sauvan, and J. Hugonin, Laser Photonics Rev. 2, 514 (2008).
- [3] K. J. Vahala, Nature (London) 424, 839 (2003).
- [4] S. L. McCall, A. F. J. Levi, R. E. Slusher, S. J. Pearton, and R. A. Logan, Appl. Phys. Lett. 60, 289 (1992).
- [5] D. W. Vernooy, A. Furusawa, N. P. Georgiades, V. S. Ilchenko, and H. J. Kimble, Phys. Rev. A 57, R2293 (1998).
- [6] D. Englund, H. Altug, B. Ellis, and J. Vucković, Laser Photonics Rev. 2, 264 (2008).
- [7] X. Yang and C. W. Wong, Opt. Express 15, 4763 (2007).
- [8] J. F. McMillan, X. Yang, N. C. Panoiu, R. M. Osgood, and C. W. Wong, Opt. Lett. **31**, 1235 (2006).
- [9] E. L. Ivchenko, M. A. Kaliteevski, A. V. Kavokin, A. I. Nesvizhskii, and A. F. Ioffe, J. Opt. Soc. Am. B 13, 1061 (1996).
- [10] G. Khitrova, H. M. Gibbs, F. Jahnke, M. Kira, and S. W. Koch, Rev. Mod. Phys. 71, 1591 (1999).
- [11] S. John and M. Florescu, J. Opt. A, Pure Appl. Opt. 3, S103 (2001).
- [12] M. Soljačić and J. D. Joannopoulos, Nature Mater. 3, 211 (2004).
- [13] M. Fleischhauer, A. Imamoglu, and J. P. Marangos, Rev. Mod. Phys. 77, 633 (2005).
- [14] M. Soljačić, E. Lidorikis, L. V. Hau, and J. D. Joannopoulos, Phys. Rev. E 71, 026602 (2005).
- [15] V. G. Arkhipkin and S. A. Myslivets, Quantum Electron. 39, 157 (2009).
- [16] M. G. Payne and L. Deng, Phys. Rev. A 64, 031802(R) (2001).

PHYSICAL REVIEW A 80, 061802(R) (2009)

- [17] S. Inouye, R. F. Löw, S. Gupta, T. Pfau, A. Görlitz, T. L. Gustavson, D. E. Pritchard, and W. Ketterle, Phys. Rev. Lett. 85, 4225 (2000).
- [18] K. Lee and N. M. Lawandy, Appl. Phys. Lett. 78, 703 (2001).
- [19] J. Sharping, Y. Okawachi, and A. Gaeta, Opt. Express 13, 6092 (2005).
- [20] D. Klyshko, Physical Basics of Quantum Electronics (Nauka, Moscow, 1986) [in Russian].
- [21] S. A. Akhmanov and N. I. Koroteev, Methods of Nonlinear Optics in Light Scattering Spectroscopy (Nauka, Moscow, 1981) [in Russian].
- [22] K. S. Repasky, L. Meng, J. K. Brasseur, J. L. Carlsten, and R. C. Swanson, J. Opt. Soc. Am. B 16, 717 (1999).
- [23] M. Poelker and P. Kumar, Opt. Lett. 17, 399 (1992).
- [24] A. Shen, *The Principles of Nonlinear Optics* (John Wiley and Sons, Inc., New York, 1984).
- [25] A. Yariv, *Quantum Electronics*, 2nd ed. (Wiley, New York, 1975).
- [26] R. Boyd, Nonlinear Optics (Academic Press, London, 1992).
- [27] A. V. Balakin, V. A. Bushuev, B. I. Mantsyzov, I. A. Ozheredov, E. V. Petrov, A. P. Shkurinov, P. Masselin, and G. Mouret, Phys. Rev. E 63, 046609 (2001).
- [28] A. Yariv, Introduction to Optical Electronics, 2nd ed. (Holt, Rinehart and Winston, New York, 1976).
- [29] K. S. Repasky, J. K. Brasseur, L. Meng, and J. L. Carlsten, J. Opt. Soc. Am. B 15, 1667 (1998).
- [30] Y. Shimizu, N. Shiokawa, N. Yamamoto, M. Kozuma, T. Kuga, L. Deng, and E. W. Hagley, Phys. Rev. Lett. 89, 233001 (2002).
- [31] J. Zhang, G. Hernandez, and Y. Zhu, Opt. Lett. 33, 46 (2008).