

**Publisher's Note: Model-based optimization of tapered free-electron lasers
[Phys. Rev. ST Accel. Beams **18**, 040702 (2015)]**

Alan Mak, Francesca Curbis, and Sverker Werin
(Received 3 November 2017; published 17 November 2017)

DOI: [10.1103/PhysRevAccelBeams.20.119902](https://doi.org/10.1103/PhysRevAccelBeams.20.119902)

This paper was published online on 23 April 2015 with an omission of an Acknowledgment section, as well as typographical errors in Eq. (2) and the caption to Fig. 1.

Equation (2) should read as

$$a_w = \frac{K}{\sqrt{2}} \equiv \frac{e\lambda_w B_w}{2\sqrt{2}\pi m_e c}$$

The third line of the caption to Fig. 1 should read as "... trapping fraction, and (f) the bunching factor. The ...". The Acknowledgment section should be placed on page 11 and read as "The simulations presented in this article were performed on resources provided by the Swedish National Infrastructure for Computing (SNIC) at Lund University." The paper has been corrected as of 10 November 2017.

Published by the American Physical Society under the terms of the [Creative Commons Attribution 4.0 International](https://creativecommons.org/licenses/by/4.0/) license. Further distribution of this work must maintain attribution to the author(s) and the published articles title, journal citation, and DOI.