# Multiple magnetic barriers in graphene

Luca Dell'Anna<sup>1</sup> and Alessandro De Martino<sup>2,3</sup>

<sup>1</sup>International School for Advanced Studies, SISSA-ISAS, I-34014 Trieste, Italy

<sup>2</sup>Institut für Theoretische Physik, Universität zu Köln, D-50937 Köln, Germany

<sup>3</sup>Institut für Theoretische Physik, Heinrich-Heine-Universität, D-40225 Düsseldorf, Germany

(Received 8 August 2008; revised manuscript received 25 September 2008; published 26 January 2009)

We study the behavior of charge carriers in graphene in inhomogeneous perpendicular magnetic fields. We consider two types of one-dimensional magnetic profiles, uniform in one direction: a sequence of N magnetic barriers and a sequence of alternating magnetic barriers and wells. In both cases, we compute the transmission coefficient of the magnetic structure by means of the transfer-matrix formalism and the associated conductance. In the first case the structure becomes increasingly transparent upon increasing N at fixed total magnetic flux. In the second case we find strong wave-vector filtering and resonant effects. We also calculate the band structure of a periodic magnetic superlattice and find a wave-vector-dependent gap around zero energy.

DOI: 10.1103/PhysRevB.79.045420

PACS number(s): 73.21.-b, 73.63.-b, 75.70.Ak

## I. INTRODUCTION

The electronic properties of graphene<sup>1</sup> in the presence of inhomogeneous perpendicular magnetic fields have very recently attracted considerable theoretical attention.<sup>2–11</sup> In graphene the charge carriers close to the Fermi points *K* and *K'* form a relativistic gas of chiral massless [Dirac-Weyl (DW)] quasiparticles with a characteristic conical spectrum. This has far-reaching consequences. For example, quasiparticles in graphene are able to tunnel through high and wide electrostatic potential barriers, a phenomenon often referred to as Klein tunneling and related to their chiral nature.<sup>12</sup> Moreover, in a uniform magnetic field, graphene exhibits an unconventional half-integer quantum Hall effect,<sup>13</sup> which can be understood in terms of the existence, among the relativistic Landau levels formed by the quasiparticles, of a zero-energy one.<sup>14</sup>

From a theoretical perspective, it is then interesting to explore how the DW nature of the charge carriers affects their behavior in nonuniform magnetic fields. Such investigation has been started in Ref. 2, and here we generalize and expand on it by studying several more complex geometries.

Experimentally, inhomogeneous magnetic profiles on submicron scales in ordinary two-dimensional electron gases (2DEGs) in semiconductor heterostructures have been produced in several ways, and magnetic barriers with heights up to 1 T have been obtained. One approach exploits the fringe field produced by ferromagnetic stripes fabricated on top of the structure.<sup>15</sup> Another possibility consists in applying a uniform magnetic field to a 2DEG with a step.<sup>16</sup> In yet another approach, a film of superconducting material with the desired pattern is deposited on top of the structure, and a uniform magnetic field is applied.<sup>17</sup> In this way, magnetic structures with different geometries have been experimentally realized, and their mesoscopic transport properties have been studied, e.g., transport through single magnetic barriers<sup>18</sup> and superlattices,<sup>19</sup> magnetic edge states close to a magnetic step,<sup>20</sup> and magnetically confined quantum dots or antidots.<sup>21</sup> Correspondingly, there exists an extensive theoretical literature,<sup>22</sup> which elucidates the basic mechanisms underlying the behaviors observed in experiments.

In principle, the same concepts and technologies can be used to create similar magnetic structures in graphene once the graphene sheet is covered by an insulating layer, which has recently been demonstrated feasible.<sup>23,24</sup> Although at the time of writing there is yet no published experimental work demonstrating magnetic barriers in graphene, this should be within reach of present-day technology, which provides motivation for the present work.

In a previous paper<sup>2</sup> we showed that, in contrast to electrostatic barriers, a single magnetic barrier in graphene totally reflects an incoming electron, provided the electron energy does not exceed a threshold value related to the total magnetic flux through the barrier. Above this threshold, the transmission coefficient strongly depends on the incidence angle.<sup>2,8</sup> These observations were used to argue that charge carriers in graphene can be confined by means of magnetic barriers, which may thus provide efficient tools to control the transport properties in future graphene-based nanodevices.

Here we focus on more complex multiple barrier configurations and magnetic superlattices. We consider two types of one-dimensional profiles. In the first case the magnetic field in the barrier regions is always assumed to point upward, while in the second it points alternatingly upward and downward. We shall see that there are sharp differences in the transport properties of the two cases. In particular, in the up-down geometry we find a much stronger angular dependence of the transmission coefficient, which leads to an interesting wave-vector filter effect.

The outline of the paper is the following. In Sec. II we introduce the Dirac-Weyl Hamiltonian for graphene, the two types of magnetic profiles we consider in the rest of the paper, and the transfer-matrix formalism for Dirac-Weyl particles. In Secs. III and IV we compute and discuss the transmission coefficient separately for the two cases. In Sec. V we consider a periodic magnetic superlattice and determine its band structure. Finally, in Sec. VI we summarize our results and draw our conclusions.

## **II. HAMILTONIAN AND TRANSFER MATRIX**

Electrons in clean graphene close to the two Fermi points K and K' are described by two decoupled copies of the



FIG. 1. Magnetic profile Eq. (3): N magnetic barriers of width  $d_B$  separated by nonmagnetic regions of width  $d_0$ .

Dirac-Weyl equation. We shall focus here on a single valley and neglect the electron spin.<sup>25</sup> Including the perpendicular magnetic field via minimal coupling, the DW equation reads

$$v_F \boldsymbol{\sigma} \cdot \left( -i\hbar \nabla + \frac{e}{c} \mathbf{A} \right) \Psi = E \Psi, \qquad (1)$$

where  $\boldsymbol{\sigma} = (\sigma_x, \sigma_y)$  are Pauli matrices acting in sublattice space and  $v_F = 8 \times 10^5$  m/s is the Fermi velocity in graphene. In the Landau gauge, A = (0, A(x)), with  $B_z = \partial_x A$ , the y component of the momentum is a constant of motion, and the spinor wave function can be written as  $\Psi(x, y) = \psi(x)e^{ik_y y}$ , whereby Eq. (1) is reduced to a one-dimensional problem,

$$\begin{pmatrix} -E & -i\partial_x - i[k_y + A(x)] \\ -i\partial_x + i[k_y + A(x)] & -E \end{pmatrix} \psi = 0.$$
(2)

Equation (2) is written in dimensionless units: with *B* the typical magnitude of the magnetic field, and  $\ell_B = \sqrt{\hbar c/eB}$  the associated magnetic length, we express the vector potential A(x) in units of  $B\ell_B$ , the energy *E* in units of  $\hbar v_F/\ell_B$ , and *x* and  $k_y$ , respectively, in units of  $\ell_B$  and  $\ell_B^{-1}$ . The values of local magnetic fields in the barrier structures produced by ferromagnetic stripes range up to 1 T, with typical values of the order of tenth of tesla. For  $B \approx 0.1$  T, we find  $\ell_B \approx 80$  nm and  $\hbar v_F/\ell_B \approx 7$  meV, which set the typical length and energy scales.

We shall consider two types of magnetic field profiles. In the first case, illustrated in Fig. 1, the profile consists of a sequence of N magnetic barriers of equal height B (assumed positive for definiteness) and width  $d_B$ , separated by nonmagnetic regions of width  $d_0$ . The vector potential is then chosen as

$$A(x) = \begin{cases} 0, & x \in [-\infty, 0] \\ nd_B + (x - x_n), & x \in [x_n, x_n + d_B] \\ (n+1)d_B, & x \in [x_n + d_B, x_{n+1}] \\ Nd_B, & x \in [x_N, \infty], \end{cases}$$
(3)

where n=0,...,N-1 and  $x_n=n(d_0+d_B)$ . The quantity  $Nd_B$  is the total magnetic flux through the structure per unit length



FIG. 2. Magnetic profile Eq. (4): N magnetic barriers of width  $d_B$  separated by magnetic wells of width  $d_{-B}$ .

in the y direction.<sup>26</sup> We shall refer to this profile as the multiple barriers case and discuss it in Sec. III.

In the second case, illustrated in Fig. 2, each magnetic barrier is followed by a region of width  $d_{-B}$  of opposite magnetic field. The vector potential is accordingly chosen as

$$A(x) = \begin{cases} 0, & x \in [-\infty, 0] \\ nD + (x - x_n), & x \in [x_n, x_n + d_B] \\ nD + (2d_B + x_n - x), & x \in [x_n + d_B, x_{n+1}] \\ ND, & x \in [x_N, \infty], \end{cases}$$
(4)

where n=0, ..., N-1,  $x_n=n(d_B+d_{-B})$ , and  $D=d_B-d_{-B}$ . We shall refer to this profile as the alternating barrier-well case and discuss it in Sec. IV. The parameter *D* has the meaning of net magnetic flux through a cell formed by a barrier and a well. For D=0 this profile can be extended to a periodic magnetic superlattice, a case considered in Sec. V.

With our gauge choice, the value of the vector potential on the right of the structure is equal to the total magnetic flux  $\Phi$  through it

$$\Phi \equiv A(x > x_N) = \begin{cases} Nd_B, & \text{case 1} \\ N(d_B - d_{-B}), & \text{case 2}, \end{cases}$$
(5)

which is an important control parameter for the transport properties. In both cases, the solutions to Eq. (2) can be obtained by first writing the general solution in each region of constant  $B_z$  as linear combination (with complex coefficients) of the two independent elementary solutions, and then imposing the continuity of the wave function at the interfaces between regions of different  $B_z$  to fix the complex coefficients. This procedure is most conveniently performed in the transfer-matrix formalism. Here we directly use this approach and refer the reader to Refs. 27 and 28 for a detailed discussion.

The transfer matrix,

$$\hat{T} = \begin{pmatrix} T_{11} & T_{12} \\ T_{21} & T_{22} \end{pmatrix},$$
(6)

relates the wave function on the left side of the magnetic structure  $(x < x_0=0)$ ,

$$\psi(x) = \left(\frac{1}{\frac{k_x^i + ik_y}{E}}\right) e^{ik_x^i x} + r \left(\frac{1}{\frac{-k_x^i + ik_y}{E}}\right) e^{-ik_x^i x}, \quad (7)$$

where  $k_x^i = \sqrt{E^2 - k_y^2}$ , to the wave function on the right side  $(x > x_N)$ ,

$$\psi(x) = t \sqrt{\frac{k_x^i}{k_x^f}} \left( \frac{1}{\frac{k_x^f + i(k_y + \Phi)}{E}} \right) e^{ik_x^f x},$$
(8)

where  $k_x^f = \sqrt{E^2 - (k_y + \Phi)^2}$ . The coefficients *r* and *t* are, respectively, the reflection and transmission amplitudes, and we used that with our gauge choices [Eqs. (3) and (4)], the vector potential vanishes on the left of the magnetic structure and on the right side is equal to  $\Phi$ . As usual, the factor  $\sqrt{k_x^i/k_x^f}$  ensures proper normalization of the probability current. The relation which expresses the continuity of the wave function is then given by<sup>29,30</sup>

$$\begin{pmatrix} 1 \\ r \end{pmatrix} = \hat{T} \begin{pmatrix} \sqrt{k_x^i / k_x^f} t \\ 0 \end{pmatrix}.$$
 (9)

Solving Eq. (9) for t, we get the transmission probability T as

$$\mathcal{T}(E,k_y) = |t|^2 = \frac{k_x^J}{k_x^i} \frac{1}{|T_{11}|^2}.$$
 (10)

Once  $\mathcal{T}(E, k_y)$  is known, it is straightforward to compute the zero-temperature conductance by integrating  $\mathcal{T}$  over one-half of the (Fermi) energy surface,<sup>31</sup>

$$G(E) = G_0 \int_{-\pi/2}^{\pi/2} d\phi \cos \phi \, \mathcal{T}(E, E \sin \phi), \qquad (11)$$

where  $\phi$  is the incidence angle (we measure angles with respect to the *x* direction), defined by  $k_y = E \sin \phi$  and  $G_0 = 2e^2 E L_y / \pi h$ .  $L_y$  is the length of the graphene sample in the *y* direction and  $G_0$  includes a factor 4 coming from the spin and valley degeneracies.

Before proceeding with the calculations, we can derive a simple and general condition for a nonvanishing transmission. For this purpose it is convenient to parametrize the momenta in the leftmost and rightmost regions, respectively, in terms of incidence and emergence angles,  $\phi$  and  $\phi_{f}$ ,

$$k_x^l = E \cos \phi, \quad k_y = E \sin \phi, \tag{12}$$

$$k_x^f = E \cos \phi_f, \quad k_y = E \sin \phi_f - \Phi. \tag{13}$$

The emergence angle is then fixed by the conservation of  $k_y$ ,

$$\sin \phi = \sin \phi_f - \frac{\Phi}{E}.$$
 (14)

Equation (14) implies that transmission through the structure is only possible if  $\phi_i$  satisfies the condition

$$\left|\sin\phi + \frac{\Phi}{E}\right| \le 1. \tag{15}$$

This condition, already discussed in Ref. 2 for the case of a single barrier, is in fact completely general and independent

of the detailed form of the magnetic field profile. It only requires that the magnetic field vanishes outside a finite region of space. For  $|\Phi/E| > 2$ , it implies that the magnetic structure completely reflects both quasiparticles and quasiholes. As a consequence of this angular threshold, the conductance has an upper bound given by

$$G_s(E) \equiv G_0 \left( 2 - \left| \frac{\Phi}{E} \right| \right) \theta(2|E| - |\Phi|), \tag{16}$$

with the Heaviside step function  $\theta$ . If the vector potential profile is monotonous,  $G_s$  also coincides with the classical conductance, obtained by setting  $\mathcal{T}=\theta(1-|\sin\phi+\Phi/E|)$ . If, however, A(x) is not monotonous, the classical conductance is obtained by replacing  $|\Phi|$  in Eq. (16) with the maximal value of |A| in the structure since a classical particle is totally reflected as soon as  $|A|_{\text{max}}$  (rather than the total flux  $|\Phi|$ ) exceeds twice the energy.

Before moving to Sec. III, we notice, as an aside remark, that Eq. (2) can easily be solved in closed form for E=0. The zero-energy spinors are then given by

$$\psi_{+} \propto \begin{pmatrix} 1 \\ 0 \end{pmatrix} e^{k_{y}x + \int^{x} A(x')dx'}, \tag{17}$$

$$\psi_{-} \propto \binom{0}{1} e^{-k_y x - \int^x A(x') dx'}.$$
 (18)

These wave functions are admissible if and only if they are normalizable, which depends on the sign of  $k_v$  and the behavior of the magnetic field at  $x \rightarrow \pm \infty$ . In fact, for any A(x), at most one among  $\psi_{\perp}$  and  $\psi_{\perp}$  is admissible. If the magnetic field vanishes outside a finite region of space, as in our case, one can always choose a gauge in which A(x)=0 on the left of the magnetic region and  $A(x) = \Phi$  on its right. It is then straightforward to check that for  $0 < k_v < -\Phi$ , the only normalizable solution is Eq. (17), whereas for  $-\Phi < k_v < 0$ , the normalizable solution is Eq. (18). In particular, we find that when the net magnetic flux through the structure vanishes, there exist no zero-energy states. This is nicely confirmed by the calculation of the spectrum of the periodic magnetic superlattice in Sec. V. The zero-energy state is a bound state localized in the structure. Additional bound states of higher energy may also occur,<sup>8</sup> but we do not further investigate this problem here.

## **III. MULTIPLE BARRIERS**

In this section we focus on the magnetic profile in Eq. (3). In order to compute the transfer matrix  $\hat{T}$ , we need the two elementary solutions of the DW [Eq. (2)] for  $B_z=0$  and the two for  $B_z=1$ .

We can then construct the  $2 \times 2$  matrices  $W_0(x)$  and  $W_B(x)$ , whose columns are given by the spinor solutions. In the nonmagnetic regions we have



FIG. 3. (Color online) Angular dependence of the transmission probability at E=1, through N=1,2,3,10 barriers of width  $d_B = 1/N$  (keeping in this way constant the flux  $\Phi=Nd_B=1$ ) and spaced by  $d_0=10$ .

$$\mathcal{W}_{0}(x) = \begin{pmatrix} e^{ik_{x}x} & e^{-ik_{x}x} \\ \frac{k_{x} + i(k_{y} + A)}{E} e^{ik_{x}x} & \frac{-k_{x} + i(k_{y} + A)}{E} e^{-ik_{x}x} \end{pmatrix},$$
(19)

where  $k_x(x) = \sqrt{E^2 - [k_y + A(x)]^2}$ . In the regions with  $B_z = 1$  we have

$$\mathcal{W}_{B}(x) = \begin{pmatrix} D_{p}(q) & D_{p}(-q) \\ i\sqrt{2} \\ \frac{i\sqrt{2}}{E} D_{p+1}(q) & \frac{-i\sqrt{2}}{E} D_{p+1}(-q) \end{pmatrix}, \quad (20)$$

where  $q = \sqrt{2}[A(x) + k_y]$ ,  $p = E^2/2 - 1$ , and  $D_p(q)$  is the parabolic cylinder function.<sup>32</sup> These matrices play the role of partial transfer matrices and allow us to express the condition of continuity of the wave function at each interface between the nonmagnetic and the magnetic regions. After straightforward algebra, we get

$$\hat{T} = \hat{T}_0 \hat{T}_1 \dots \hat{T}_{N-1},$$
 (21)

where



FIG. 4. The conductance  $G/G_0$  at E=1 for several values of N with  $d_B=1/N$ , such that  $\Phi=1$ , and  $d_0=10$  (black dots linked by long-dashed line, which is a guide for the eyes only). The upper bound (dashed line) corresponds to the classical value  $G_s/G_0=1$  [see Eq. (16)] while the dotted line is the curve given by Eq. (26) as a function of N.



FIG. 5. (Color online) Angular dependence of the transmission probability, for different values of *E*, fixing  $d_B=1$ ,  $d_0=10$ , and N=6.

$$\hat{T}_n = \mathcal{W}_0^{-1}(x_n)\mathcal{W}_B(x_n)\mathcal{W}_B^{-1}(x_n + d_B)\mathcal{W}_0(x_n + d_B)$$
(22)

is the transfer matrix<sup>29</sup> across the (n+1)th barrier, and we remind that  $x_n = n(d_0 + d_R)$ .

From Eqs. (10), (21), and (22) we numerically evaluated the transmission probability  $\mathcal{T}$  for various sets of parameters. The results are illustrated in Figs. 3, 5, and 7. Figure 3 shows the angular dependence of the transmission coefficient at fixed energy for several values of N, but keeping constant the magnetic flux  $\Phi$  through the structure. In agreement with the discussion in Sec. II and Eq. (15), we observe that the range of angles where  $\mathcal{T} \neq 0$  remains the same,  $\phi \leq 0$ , upon increasing the number of barriers. At the same time, however, the transmission itself is modified, and oscillations appear, whose number increases with N and for larger separations between the barriers.

More remarkably we find that rarefying the magnetic field by adding more barriers without changing the total flux  $\Phi$ , the transmission probability approaches the classical limit, where it is zero or one depending on whether the incidence angle exceeds or not the angular threshold; see Fig. 3. Correspondingly, the conductance as a function of *N* approaches the classical limit [Eq. (16)]; see Fig. 4. As expected, the same limit is also approached upon increasing the energy especially for large *N*. This is clearly illustrated in Fig. 5 for the transmission, and in Fig. 6 for the conductance: one sees



FIG. 6. The conductance as a function of the energy for N=6 barriers with  $d_B=1$  and  $d_0=10$  (solid line). The dashed line is the curve given by the classical limit Eq. (16).



FIG. 7. (Color online) Angular dependence of the transmission probability, for different values of  $d_B$ , fixing E=2,  $d_0=10$ , and N=3.

that already for six barriers the classical limit provides a very good approximation. The classical limit is instead hardly achieved changing  $d_B$ , except when  $d_B$  is close to the extreme values 0 and E/N; see Figs. 7 and 8.

In conclusion the main result of this section is that, at fixed flux  $\Phi$ , the larger is the number of barriers, the more transparent is the magnetic structure. This is a purely quantum-mechanical effect, peculiar to magnetic barriers.

Qualitatively this behavior can be explained as follows. To calculate the probability for a relativistic particle to go through a very thin single barrier, we can simulate the profile of A with a step function with height  $\Phi/N$  in order to have the same flux of a magnetic barrier with width  $d_B = \Phi/N$ . In this case the transfer matrix is simply

$$\hat{T} = \mathcal{W}_0(0^{-})^{-1} \mathcal{W}_0(0^{+}), \qquad (23)$$

where  $\mathcal{W}_0(0^-)$  is given by Eq. (19) with A=0 and  $k_x = k_x^i$ , while in  $\mathcal{W}_0(0^+)$  we have  $A = \Phi/N$  and consequently  $k_x = k_x^i$ . From Eq. (10) we get the following transmission probability for a single barrier:

$$\mathcal{T}_1(\phi) \simeq \frac{4\cos\phi\cos\phi_f\,\theta(1-|\sin\phi+\Phi/NE|)}{(\cos\phi+\cos\phi_f)^2 + [\Phi/(NE)]^2},\quad(24)$$

where  $\phi_f$  is defined by  $E \sin \phi_f = E \sin \phi + \Phi/N$ . For N barriers we can roughly estimate the probability for the particle to cross the magnetic structure to be



FIG. 8. The conductance as a function of  $d_B$  for N=3 barriers with E=2 and  $d_0=10$  (solid line). The dashed line is the curve given by the classical limit Eq. (16).

$$\mathcal{T}_{N}(\phi) \sim \mathcal{T}_{1}(\phi)^{N} \theta(1 - |\sin \phi + \Phi/E|), \qquad (25)$$

where we have put by hand the global constraint of momentum conservation. Using the expression above we can then calculate the conductance applying Eq. (11). To simplify the calculation, in order to have a qualitative description of the conductance behavior, we further approximate  $\cos \phi_f$  $\approx \cos \phi$  in Eq. (24), valid for small  $\Phi/N$ , and replace  $\cos^2 \phi$ with its average 1/2, getting at the end an approximated expression for *G* which reads

$$G \simeq G_s \left(\frac{2N^2 E^2}{2N^2 E^2 + \Phi^2}\right)^N,$$
 (26)

being  $\Phi$  the total flux for *N* barriers. In Fig. 4 we compare the exact calculation with the approximate one given by Eq. (26) and find a surprisingly good agreement. The small discrepancy has various possible sources: the angular dependence of the transmission, which is averaged out in the approximate calculation; the finite width of the barriers; and the finite separations among the barriers, which may let the particles bounce back and forth, in this way reducing the transmission. This latter effect, therefore, suppresses a bit the conductance predicted by Eq. (26).

### **IV. ALTERNATING MAGNETIC BARRIERS AND WELLS**

Next, we consider the magnetic profile in Eq. (4), illustrated in Fig. 2. In order to construct the transfer matrix in this case we need  $W_B$  and the partial transfer matrix for the regions with  $B_z = -B$ , which is given by

$$\mathcal{W}_{-B}(x) = \begin{pmatrix} D_{p+1}(-q) & D_{p+1}(q) \\ -\frac{i\sqrt{2}}{E}(p+1)D_p(-q) & \frac{i\sqrt{2}}{E}(p+1)D_p(q) \end{pmatrix}.$$
(27)

After some algebra, we then get

$$\hat{T} = \mathcal{W}_0^{-1}(x_0)\mathcal{W}_{-B}(x_0)\hat{T}_0\hat{T}_1\dots\hat{T}_{N-2}\hat{T}_{N-1}\mathcal{W}_{-B}^{-1}(x_N)\mathcal{W}_0(x_N),$$
(28)

where

$$\hat{T}_{n} = \mathcal{W}_{-B}^{-1}(x_{n})\mathcal{W}_{B}(x_{n})\mathcal{W}_{B}^{-1}(x_{n}+d_{B})\mathcal{W}_{-B}(x_{n}+d_{B})$$
(29)

is the transfer matrix<sup>29</sup> across the (n+1)th magnetic barrier and  $x_n = n(d_B + d_{-B})$ . Note that Eq. (29) differs from Eq. (22) since now on the right and on the left of a magnetic barrier there is a magnetic well rather than a nonmagnetic region. As in Sec. III, the numerical evaluation of  $\hat{T}$  is straightforward, and the results for the transmission probability and for the conductance are illustrated in Figs. 9–15.

Figure 9 shows the angular dependence of  $\mathcal{T}$  for a single block consisting of a barrier followed by a well of different width. The plot emphasizes the very strong wave-vector dependence of the transmission and shows that by tuning  $d_B$  and  $d_{-B}$  one can achieve very narrow transmitted beams. This suggests an interesting application of this structure as a magnetic filter, where only quasiparticles incident with an



FIG. 9. (Color online) Angular dependence of the transmission probability at E=6 through a structure consisting of one magnetic barrier of width  $d_B$  and one magnetic well of width  $d_{-B}$ . We fix  $d_{-B}=11.7\approx 2E$  and vary  $d_B$  from 0 to  $5.8\approx E$ .

angle within a very small range are transmitted.

More explicitly, in order to select a narrow beam at an angle  $0 < \phi < \frac{\pi}{2}$  (at fixed energy), one can choose the widths such that

$$\frac{d_B}{E} = (1 - \sin \phi) - \varepsilon_1, \qquad (30)$$

$$\frac{d_{-B}}{E} = 2 - \varepsilon_2, \tag{31}$$

with  $\varepsilon_{1,2} \ll 1$ . With this choice,  $\phi$  is very close to the angular threshold for the first barrier, and the well is close to be totally reflecting. The combination of these two effects leads to the narrow beam. For  $-\frac{\pi}{2} < \phi < 0$  it is enough to flip the magnetic field. These relations hold better at small values of  $|\phi|$ . In the rest of this section, we focus on structures with  $d_B = d_{-B}$ , i.e., when the total magnetic flux through the structure vanishes.

For several blocks of barriers and wells we observe an interesting *recursive effect* shown in Fig. 10. There are angles at which, upon increasing N, the transmission takes at most  $N_m$  values, where  $N_m$  is the smallest number of blocks for which the transmission is perfect (i.e., T=1). Some of these angles are emphasized in Fig. 10 by dashed lines. At those angles, for instance, magnetic structures with N equal to integer multiples of 2, 3, and 5 exhibit perfect transmission even for small energy.



FIG. 10. (Color online) Angular dependence of the transmission probability at E=1 and  $d_B=d_{-B}=1$  for several values of *N*. The black dashed lines correspond to the angles for recursive transmission of multiplicity 2 (at  $\phi \approx \pi/18$ ), 3 (at  $\phi = -\pi/6$ ), and 5 (at  $\phi \approx -\pi/54$  and  $\phi \approx -7\pi/18$ ).



FIG. 11. The conductance  $G/G_0$  at E=1 varying N with  $d_B = d_{-B} = 1$ . In the inset  $d_B = d_{-B} = 0.8$  in the same range of N.

These effects can be understood as follows. Suppose that, at a given angle, the transmission probability through  $N_m$ cells has a resonance and reach the value 1. Then, for any sequence consisting of a number of cells equal to an integer multiple of  $N_m$ , the transmission is 1 again. (It is crucial here that since the magnetic flux through each block is zero, the emergence angle always coincides with the incidence angle.) At such an angle, then, T can only take, upon changing N, at most  $N_m$  values. Notice that perfect transmission occurs also for low energy of the incident particle, and the angular spreading of perfect transmission is also reduced by adding multiple blocks.

This effect in the transmission also reflects in the conductance. Figure 11 shows that, for a particular set of parameters, *G* oscillates as a function of *N* with period 3. However, for a different value of  $d_B$ , shown in the inset, the period is 2. This unexpectedly strong dependence of the conductance on adding or removing blocks of barriers and wells could be exploited to design a magnetic switch for charge carriers in graphene. Moreover, we observe that the angular dependence of the transmission is abruptly modified also by changing the energy *E* of the incident particles (see Fig. 12) or the width of the barriers  $d_B$  (Fig. 14) where we observe pronounced resonance effects. As a consequence the conductance exhibits a modulated profile as a function of both the energy and the barrier's width, as illustrated, respectively, in Figs. 13 and 15.



FIG. 12. (Color online) Angular dependence of the transmission probability for several values of the energy *E*, for  $d_B=d_{-B}=1$  and N=6.



FIG. 13. The conductance  $G/G_0$  as a function of the energy *E* for N=6 with  $d_B=d_{-B}=1$  (solid line). The dashed line is the classical limit, i.e.,  $(2-d_B/E)\theta(2E-d_B)$ .

#### **V. PERIODIC MAGNETIC SUPERLATTICE**

We now focus on the case of a periodic magnetic superlattice. We observe that, if  $d_B = d_{-B}$ , the profile [Eq. (4)] can be extended to a periodic profile, illustrated in Fig. 16, where the elementary unit is given by the block formed by a barrier and a well. Imposing periodic boundary conditions on the wave function after a length  $L=x_N=N\ell$  (where  $\ell=2d_B$ ), i.e.,  $\psi(x_0)=\psi(x_N)$ , and defining the matrix,

$$\Omega = \mathcal{W}_B^{-1}(0)\mathcal{W}_{-B}(0)\mathcal{W}_{-B}^{-1}(d_B)\mathcal{W}_B(d_B), \qquad (32)$$

standard calculations<sup>27</sup> lead to the quantization condition for the energy,

$$2\cos(K_r\ell) = \operatorname{Tr}\Omega.$$
(33)

At fixed  $k_y$ , Eq. (33) gives the energy as a function of the Bloch momentum  $K_x = \frac{2\pi n}{L}$ . Notice that  $K_x$  is related to the periodicity of the structure and parametrizes the spectrum. It should not be confused with the *x* component of the momentum  $k_x$  used in Secs. II–IV. Figure 17 illustrates the first two bands as a function of  $K_x$  for two values of  $k_y$ . Figure 18 shows the contour plot for Tr  $\Omega$  as a function of *E* and  $k_y$ . We find two interesting main features. First, around zero energy there is a gap, whose width decreases for larger values of  $|k_y|$ . This is in agreement with the fact that for a magnetic profile with zero total flux there exist no zero-energy states.







FIG. 15. The conductance  $G/G_0$  as a function of  $d_B = d_{-B}$  for N=3 with E=1. The dashed line is the classical limit.

Second, for some values of  $k_y$ , the group velocity  $v_y = \frac{\partial E}{\partial k_y}$  diverges (see Fig. 18 close to  $|k_y| > |E| \approx 0.3$ ). The property of *superluminal* velocity has already been observed for massless Klein-Gordon bosons in a periodic scalar potential.<sup>28</sup> In this work, such property has been observed for massless Dirac-Weyl fermions in a periodic vector potential.

### VI. SUMMARY AND CONCLUSIONS

In this paper we have studied the transmission of charge carriers in graphene through complex magnetic structures consisting of several magnetic barriers and wells and the related transport properties. We focused on two different types of magnetic profiles. In the case of a sequence of magnetic barriers, we have found that the transparency of the structure is enhanced when the same total magnetic flux is distributed over an increasing number N of barriers. The transmission probability and the conductance then approach the classical limit for large N; see in particular Figs. 3 and 4.

The behavior of alternating barriers and wells turns out to be even more interesting. We have shown that a single unit consisting of a barrier and a well of suitable widths can be used as a very efficient wave-vector filter for Dirac-Weyl quasiparticles; see Fig. 9. With several blocks we have ob-



FIG. 16. Periodic superlattice of alternating magnetic barriers and wells with  $d_B = d_{-B}$ .



FIG. 17. The spectrum for the periodic superlattice in Fig. 16 with  $d_B = d_{-B} = 1$  at  $k_y = 0$  (full points) and  $k_y = 1$  (cross poins).  $K_x$  is the Bloch momentum.

served strong resonant effects, such that at given angles one gets narrow beams perfectly transmitted even for low energy of the incident quasiparticles; see Fig. 10. As a result, the conductance is drastically modified by adding or removing blocks; see Fig. 4. This suggests possible applications as magnetic switches for charge carriers in graphene.

Since most of our results concern the angular dependence of the transmission coefficient, a comment on the possibility to measure it is in order here. Such measurement should, in principle, be feasible, following for example ideas put forward in Ref. 33. The idea consists in using a small electric contact [for example, the tip of a scanning tunneling microscope (STM)] to inject electrons in the graphene sheet on one side of the magnetic structure, and a second local contact on the other side as a probe to detect the transmitted electrons. The current measured between the two contacts would then reflect the transmission probability through the structure. If the contacts are made smaller than the de Broglie wavelength of the electrons (which is large for small doping, the situation considered here), then one may be able to resolve the spatial structure of the local current distribution and



FIG. 18. (Color online) The allowed spectrum,  $|\text{Tr }\Omega| \le 2$ , varying *E* and  $k_y$ , at  $d_B = d_{-B} = 1$ . The contour lines correspond to the values of Tr  $\Omega$  in the interval [-2, 2] at steps of 0.5, increasing from blue (inner dark gray) to red (outer dark gray).

thus get information on the angular dependence of  $\mathcal{T}$ . We hope that our paper will further stimulate experimental work on the rich physics of magnetic structures in graphene.

### **ACKNOWLEDGMENTS**

We thank R. Egger and W. Häusler for several valuable discussions. This work was supported by the MIUR project "Quantum noise in mesoscopic systems," by the SFB Transregio 12 of the DFG, and by the ESF network INSTANS.

- <sup>1</sup>For recent reviews, see A. K. Geim and K. S. Novoselov, Nature Mater. **6**, 183 (2007); A. H. Castro Neto, F. Guinea, N. M. R. Peres, K. S. Novoselov, and A. K. Geim, Rev. Mod. Phys. **81**, 109 (2009).
- <sup>2</sup> A. De Martino, L. Dell'Anna, and R. Egger, Phys. Rev. Lett. **98**, 066802 (2007); Solid State Commun. **144**, 547 (2007).
- <sup>3</sup>S. Park and H. S. Sim, Phys. Rev. B 77, 075433 (2008).
- <sup>4</sup>L. Oroszlany, P. Rakyta, A. Kormanyos, C. J. Lambert, and J. Cserti, Phys. Rev. B **77**, 081403(R) (2008).
- <sup>5</sup>T. K. Ghosh, A. De Martino, W. Häusler, L. Dell'Anna, and R. Egger, Phys. Rev. B **77**, 081404(R) (2008); W. Häusler, A. De Martino, T. K. Ghosh, and R. Egger, *ibid.* **78**, 165402 (2008).
- <sup>6</sup>F. Zhai and K. Chang, Phys. Rev. B 77, 113409 (2008).
- <sup>7</sup>M. Tahir and K. Sabeeh, Phys. Rev. B **77**, 195421 (2008).
- <sup>8</sup>M. Ramezani Masir, P. Vasilopoulos, A. Matulis, and F. M. Peeters, Phys. Rev. B **77**, 235443 (2008).

- <sup>9</sup>Hengyi Xu, T. Heinzel, M. Evaldsson, and I. V. Zozoulenko, Phys. Rev. B 77, 245401 (2008).
- <sup>10</sup>A. Kormányos, P. Rakyta, L. Oroszlány, and J. Cserti, Phys. Rev. B **78**, 045430 (2008).
- <sup>11</sup>S. Ghosh and M. Sarma, arXiv:0806.2951 (unpublished).
- <sup>12</sup>M. I. Katsnelson, K. S. Novoselov, and A. K. Geim, Nat. Phys. 2, 620 (2006); V. V. Cheianov and V. I. Fal'ko, Phys. Rev. B 74, 041403(R) (2006).
- <sup>13</sup>K. S. Novoselov, A. K. Geim, S. V. Morozov, D. Jiang, M. I. Katsnelson, I. V. Grigorieva, S. V. Dubonos, and A. A. Firsov, Nature (London) **438**, 197 (2005); Y. Zhang, Y.-W. Tan, H. L. Stormer, and P. Kim, *ibid.* **438**, 201 (2005).
- <sup>14</sup> V. P. Gusynin and S. G. Sharapov, Phys. Rev. Lett. **95**, 146801 (2005).
- <sup>15</sup>See, for example, M. Cerchez, S. Hugger, T. Heinzel, and N.

Schulz, Phys. Rev. B **75**, 035341 (2007) for a recent work, and references therein.

- <sup>16</sup>M. L. Leadbeater, C. L. Foden, J. H. Burroughes, M. Pepper, T. M. Burke, L. L. Wang, M. P. Grimshaw, and D. A. Ritchie, Phys. Rev. B **52**, R8629 (1995).
- <sup>17</sup>S. J. Bending, K. von Klitzing, and K. Ploog, Phys. Rev. Lett. 65, 1060 (1990).
- <sup>18</sup> M. Johnson, B. R. Bennett, M. J. Yang, M. M. Miller, and B. V. Shanabrook, Appl. Phys. Lett. **71**, 974 (1997); V. Kubrak, A. Neumann, B. L. Gallagher, P. C. Main, M. Henini, C. H. Marrows, and B. J. Hickey, J. Appl. Phys. **87**, 5986 (2000).
- <sup>19</sup>H. A. Carmona, A. K. Geim, A. Nogaret, P. C. Main, T. J. Foster, M. Henini, S. P. Beaumont, and M. G. Blamire, Phys. Rev. Lett. **74**, 3009 (1995); P. D. Ye, D. Weiss, R. R. Gerhardts, M. Seeger, K. von Klitzing, K. Eberl, and H. Nickel, *ibid.* **74**, 3013 (1995).
- <sup>20</sup>A. Nogaret, S. J. Bending, and M. Henini, Phys. Rev. Lett. 84, 2231 (2000).
- <sup>21</sup>K. S. Novoselov, A. K. Geim, S. V. Dubonos, Y. G. Cornelissens, F. M. Peeters, and J. C. Maan, Phys. Rev. B 65, 233312 (2002).
- <sup>22</sup>F. M. Peeters and A. Matulis, Phys. Rev. B 48, 15166 (1993); J. Reijniers, F. M. Peeters and A. Matulis, *ibid.* 59, 2817 (1999);

For a recent review, see also S. J. Lee, S. Souma, G. Ihm, and K. J. Chang, Phys. Rep. **394**, 1 (2004) and references therein.

- <sup>23</sup>B. Huard, J. A. Sulpizio, N. Stander, K. Todd, B. Yang, and D. Goldhaber-Gordon, Phys. Rev. Lett. **98**, 236803 (2007).
- <sup>24</sup> J. R. Williams, L. Di Carlo, and C. M. Marcus, Science **317**, 638 (2007).
- <sup>25</sup>In all cases discussed in this paper, the transmission probability is the same at the two valleys.
- $^{26}$ From now on the magnetic flux always refers to the unit length in the *y* direction.
- <sup>27</sup>B. H. J. McKellar and G. J. Stephenson, Jr., Phys. Rev. C 35, 2262 (1987).
- <sup>28</sup>M. Barbier, F. M. Peeters, P. Vasilopoulos, and J. M. Pereira, Phys. Rev. B 77, 115446 (2008).
- <sup>29</sup>Note that according to the usual definition, our  $\hat{T}$  is actually the inverse of the transfer matrix.
- <sup>30</sup>I. S. Ibrahim and F. M. Peeters, Phys. Rev. B **52**, 17321 (1995).
- <sup>31</sup>A. Matulis, F. M. Peeters, and P. Vasilopoulos, Phys. Rev. Lett. 72, 1518 (1994).
- <sup>32</sup>I. S. Gradshteyn and I. M. Ryzhik, *Table of Integrals, Series, and Products* (Academic, New York, 1980).
- <sup>33</sup> V. V. Cheianov, V. Fal'ko, and B. L. Altschuler, Science **315**, 1252 (2007).