

Efficiency and its bounds for a quantum Einstein engine at maximum power

H. Yan

Department of Physics, Indiana University/IUCF, 2401 Milo B. Sampson Lane, Bloomington, Indiana 47408, USA

Hao Guo*

*Department of Physics, Southeast University, Nanjing 211189, China and**Department of Physics, University of Hong Kong, Hong Kong, China*

(Received 31 August 2012; published 27 November 2012)

We study a quantum thermal engine model for which the heat transfer law is determined by Einstein's theory of radiation. The working substance of the quantum engine is assumed to be a two-level quantum system of which the constituent particles obey Maxwell-Boltzmann (MB), Fermi-Dirac (FD), or Bose-Einstein (BE) distributions, respectively, at equilibrium. The thermal efficiency and its bounds at maximum power of these models are derived and discussed in the long and short thermal contact time limits. The similarity and difference between these models are discussed. We also compare the efficiency bounds of this quantum thermal engine to those of its classical counterpart.

DOI: [10.1103/PhysRevE.86.051135](https://doi.org/10.1103/PhysRevE.86.051135)

PACS number(s): 05.70.Ln, 05.20.-y

I. INTRODUCTION

The Carnot engine plays a crucial role in the foundations of thermodynamics. However, it cannot be realized in practice since its output power is infinitesimally small due to its reversibility. Real thermal engines cannot work as slowly as Carnot engines to preserve equilibrium and must lose energy during the working cycles due to various reasons. This makes the efficiency of real thermal engines below that of an ideal Carnot engine. To optimize the thermal engines in the real world, a lot of "realistic" models have been established and studied in the literature [1–7]. One of the most practical problems associated with the optimization of real heat engines is its efficiency at maximum power. This problem was first studied by Curzon and Ahlborn in 1975 [1]. For Carnot-like heat engines, the authors assumed that the temperature differences between the heat reservoirs and working substance are finite and fixed, thus the two heat transferring processes are not reversible anymore, while the adiabatic expansion and compression processes are still reversible. Under these assumptions, they derived the well-known Curzon-Ahlborn (CA) efficiency $\eta_{CA} = 1 - \sqrt{T_c/T_h}$, where T_h and T_c are the temperatures of the hot and cold heat reservoirs with which the working substance is in contact. Though the CA formula has a good agreement with measured efficiencies of some thermal plants, this model still has some intrinsic drawbacks. On one hand, it gives neither an exact nor constraint result for the efficiency as pointed out by the authors of Ref. [4]. On the other hand, in real-world situations the temperature differences between the working medium and heat reservoirs are not constant and the heat transferring process could be governed by some more general physical laws which can incorporate temperature changing during heat transferring processes.

In our previous work on classical engines [7], we have seen that the heat transfer law plays a crucial role on the efficiency at maximum power problem. For Carnot engines, the time periods for which the adiabatic expansion and compression

processes last are usually negligibly short, while those of the two isothermal heat transferring processes are infinitely long, therefore Carnot engines have zero output power. In real-world situations, the isothermal heat transferring processes must last for a finite period of time and obey specific heat transferring laws. In Ref. [7], we studied a thermal engine model for which Newton's cooling law is obeyed during the heat transferring processes, and derived the upper and lower bounds for the efficiency at maximum power in the long and short contact time limits, respectively. By considering the heat transferring processes during which the temperature of the working medium is close to or far from isothermal, and adjusting the ratio between the heat capacities of the heating and cooling stages, the model can simulate different types of engines including but not limited to Carnot engines.

The studies of classical thermal engines can be generalized to their quantum counterparts. Recently, different models of quantum thermal engines were extensively studied in the literature [8–12]. The efficiency of a quantum thermal engine at maximum power has also been studied by the authors of Ref. [13], where the quantum thermal engine is based on the model discussed in Ref. [14], in which the quantum thermal engine is composed of particles confined in a one-dimensional (1D) infinite potential well, and the wall of the well can expand to perform work. The derived efficiency at maximum power is a universal number.

Following the same spirit, we try to generalize our previous work to the quantum world. For simplicity and without losing generality, the working substance in our model of thermal engines is a two-level quantum system [14], which can be chosen as the lowest two levels of a 1D infinite quantum well or a 1D harmonic oscillator. Unlike the discussion in Ref. [14], the temperature rather than average energy is used to describe the thermal equilibrium state as in Ref. [8]. What is important here is that the heat transferring process between the working substance and the heat reservoir is described by Einstein's theory of radiation. This can be thought of as the quantum version of the model discussed in Ref. [7] in some way. For simplicity, we denote this kind of quantum thermal engine by "quantum Einstein engine." The constituent particles of

*guohao.ph@gmail.com

the working substance are assumed to obey three well-known distribution laws, the Maxwell-Boltzmann (MB), Fermi-Dirac (FD), and Bose-Einstein (BE) distributions. We are interested in the efficiency and its bounds at maximum power. This model might have an application in the field of quantum heat engines working with trapped ions or spin systems [15].

The organization of the paper is as follows. We first study the quantum thermal engine of which the constituent particles of the working substance obey the MB distribution. This will shed light on our successive studies on the other two models. For this model, we derive the heat transferring law based on Einstein's theory of radiation, and give the formulas of the heat and entropy transfers. As in Ref. [7], we study the efficiency at maximum power and its bounds in the long and short contact time limits. We also study quantum engines for which FD and BE distributions are applied.

II. QUANTUM EINSTEIN ENGINE ASSOCIATED WITH MB DISTRIBUTION

A. General results for heat and entropy transfers

The working substance of our quantum thermal engine is assumed to be a two-level quantum system with energy levels E_1 (low) and E_2 (high). The energy difference of the two levels is $E_2 - E_1 = h\nu$, where h is the Planck's constant. The particle numbers at low and high energy levels are N_1 and N_2 , respectively, and the fixed total particle number is given by $N_0 = N_1 + N_2$. For simplicity, we first consider the case that the constituent particles of the quantum system satisfy MB distribution at equilibrium states. Assume the initial temperature of the system is T_1 , then the initial particle distributions are

$$N_1 = N_0 \frac{1}{1 + \exp(-\beta_1 h\nu)}, \quad N_2 = N_0 \frac{1}{1 + \exp(\beta_1 h\nu)}, \quad (1)$$

where $\beta_1 = 1/k_B T_1$ and k_B is the Boltzmann constant. In our model of quantum thermal engine, the heat reservoir can be thought of as a black-body source with temperature T_2 . When the working substance or the two-level quantum system is "in contact with" a black-body source, the heat is transferred by the photon emission and absorption. This heat transferring process is described by Einstein's theory of radiation [16]

$$\frac{dN_2}{dt} = -\frac{dN_1}{dt} = BN_0 u_\nu - 2BN_2 u_\nu - AN_2 = -aN_2 + b, \quad (2)$$

where $a = 2Bu_\nu + A$, $b = BN_0 u_\nu$. A and B are the famous Einstein's coefficients, and u_ν is the spectral energy density of the black-body source. The solution of Eq. (2) is given by

$$N_2(t) = \frac{b}{a} - \left[\frac{b}{a} - N_2(0) \right] \exp(-at). \quad (3)$$

Introducing the distribution function $f(\beta) = 1/[1 + \exp(\beta h\nu)]$ for level E_2 , then we have

$$N_2(0) = N_0 f(\beta_1), \quad N_2(t \rightarrow \infty) = \frac{b}{a} = N_0 f(\beta_2). \quad (4)$$




FIG. 1. (Color online) Temperature of the working substance during the heat transferring process as a function of time. The (blue) solid [(red) dashed] line indicates the temperature changing of the working substance for the situation that the temperature (T_2) of the heat reservoir is 400 K (1000 K). For both situations, the initial temperature of the working substance is 300 K. The unit is chosen such that $A = 1$ and $h\nu/k = 1$.

At time t , we have $N_2(t) = f[\beta(t)]N_0$ where

$$f[\beta(t)] = f(\beta_2) - [f(\beta_2) - f(\beta_1)] \exp(-at). \quad (5)$$

Similarly, for level E_1 , we have $N_1(t) = \{1 - f[\beta(t)]\}N_0$. We are interested in the situation with $\beta h\nu \ll 1$, which is true if the size of the quantum well is not too small or the spring constant of the harmonic oscillator is not too large at high temperature. To the leading order of $\beta h\nu$ we get

$$f(\beta) \approx \frac{1}{2} - \frac{1}{4}\beta h\nu, \quad a = A \coth(\beta_2 h\nu/2) \approx \frac{2A}{\beta_2 h\nu}. \quad (6)$$

Therefore, Eq. (5) leads to the changing of inverse temperature

$$\beta(t) = \beta_2 - (\beta_2 - \beta_1) \exp\left[-\frac{2At}{h\nu\beta_2}\right]. \quad (7)$$

It is interesting to notice that the time constant $1/a$ depends on the temperature of the heat reservoir. If temperature is higher, less time is needed for the working substance to reach equilibrium with the heat reservoir; this phenomenon is counterintuitive as shown by Fig. 1. Note that in general Einstein's coefficient $A \propto \nu^2$ [17], then the inverse time constant a is in fact proportional to ν . Therefore the higher the energy difference $h\nu$, the longer the time is needed for the system to reach the equilibrium state.

In terms of the distribution function $f(\beta)$, the quantum entropy of the two-level system can be expressed as

$$S = -k\{f(\beta) \ln f(\beta) + [1 - f(\beta)] \ln [1 - f(\beta)]\}. \quad (8)$$

Plug in the expression of $f(\beta)$, and expand Eq. (8) in series of $\beta h\nu$

$$S = k \ln 2 - \frac{1}{8}k(\beta h\nu)^2 + O(\beta h\nu)^4. \quad (9)$$

For a heat transferring process between the initial state with inverse temperature β_0 and the final state with inverse

temperature $\beta(t)$ at time t , the heat and entropy transfers are given by

$$\begin{aligned}\Delta Q(t) &= [N_2(t) - N_{20}]h\nu \\ &= N_0h\nu\{f[\beta(t)] - f(\beta_0)\} \\ &= \frac{1}{4}N_0h^2v^2[\beta_0 - \beta(t)] + O[(\beta h\nu)^3], \\ \Delta S(t) &= \frac{1}{8}k(h\nu)^2[\beta_0^2 - \beta^2(t)] + O[(\beta h\nu)^4],\end{aligned}\quad (10)$$

where N_{20} and $N_2(t)$ are the particle numbers of the initial and final states, respectively. In the derivation of $\Delta Q(t)$, we have used the fact $dN_2 = -dN_1$. Here the entropy transfer reflect the change in the entropy of the internal distribution of the quantum engine. Generically, the energy levels of the quantum working substance during the heating and cooling stages are different since the engine must expand to perform work between the two stages. We assume that the frequencies associated with the heating and cooling stages are ν_h and ν_c , respectively, and the initial and final inverse temperatures are β_{h0} , $\beta_h(t)$ and β_{c0} , $\beta_c(t)$, respectively. Therefore, to the leading order of $\beta h\nu$ the heat and entropy transfers during the heating stage are given by

$$\begin{aligned}\Delta Q_h(t) &= \frac{1}{4}N_0h^2v_h^2[\beta_{h0} - \beta_h(t)], \\ \Delta S_h(t) &= \frac{1}{8}kh^2v_h^2[\beta_{h0}^2 - \beta_h(t)^2].\end{aligned}\quad (11)$$

Similarly, during the cooling stage we have

$$\begin{aligned}\Delta Q_c(t) &= \frac{1}{4}N_0h^2v_c^2[\beta_{c0} - \beta_c(t)], \\ \Delta S_c(t) &= \frac{1}{8}kh^2v_c^2[\beta_{c0}^2 - \beta_c(t)^2].\end{aligned}\quad (12)$$

We assume the time duration that the heating and cooling stages last are τ_h and τ_c , respectively. When the quantum engine finishes a full thermodynamical cycle, the working medium returns back to its initial state and we have $\Delta S_h(\tau_h) + \Delta S_c(\tau_c) = 0$. The power output and the efficiency of the thermal engine are given by

$$P = \frac{\Delta Q_h(\tau_h) + \Delta Q_c(\tau_c)}{\tau_h + \tau_c}, \quad \eta = 1 + \frac{\Delta Q_c(\tau_c)}{\Delta Q_h(\tau_h)}.\quad (13)$$

Here we adopt the convention that $Q > 0 (< 0)$ means absorbing (releasing) heat. As mentioned before, the working substance of the quantum engine under consideration is composed by particles at the two lowest levels of a 1D infinite quantum well or 1D harmonic oscillator. The cycles of the quantum engine are as follows.

(1) The system absorbs heat Q_h from the hot reservoir during the time period τ_h .

(2) The system expands to perform work. In the case of a 1D infinite quantum well, the width of the well expands from L_0 to L_1 . In the case of 1D harmonic oscillator, the ‘‘width’’ of the harmonic potential expands while its spring constant ‘‘shrinks’’ from k_0 to k_1 in its parameter space.

(3) The system releases heat Q_c at the cold reservoir during the time period τ_c .

(4) The system returns to its original size and temperature and the working medium returns to its original state.

B. Efficiency and its bounds in the long contact time limit

When the contact time is long enough, the working substance can exchange heat sufficiently with the reservoirs.

In this limit, $\tau_{h,c}/(\beta h\nu_{h,c}A)$ is large, and we assume the final inverse temperatures for the two stages are $\beta_h = \beta_h(\tau_h)$ and $\beta_c = \beta_c(\tau_c)$. Hence the heat transfers during the two stages are

$$\Delta Q_h = \frac{1}{4}N_0h^2v_h^2x, \quad \Delta Q_c = -\frac{1}{4}N_0h^2v_c^2y,\quad (14)$$

where $x = \beta_{h0} - \beta_h$ and $y = \beta_c - \beta_{c0}$. To the leading order of $\beta h\nu$, the constraint $\Delta S_h + \Delta S_c = 0$ gives

$$v_h^2(2\beta_h + x)x - v_c^2(2\beta_c - y)y = 0,\quad (15)$$

of which the solution is given by

$$x = \sqrt{\beta_h^2 + \frac{1}{\gamma^2}(2\beta_c - y)y} - \beta_h,\quad (16)$$

where $\gamma = \nu_h/\nu_c$. Substitute Eq. (16) to the expression of the output power

$$P = \frac{1}{4}N_0h^2\frac{v_h^2x - v_c^2y}{\tau_h + \tau_c}\quad (17)$$

and let $\partial P/\partial y = 0$, the only meaningful solution for y is found to be

$$y = \frac{\beta_c(1 + \gamma^2) - \sqrt{\beta_c^2(1 + \gamma^2) + \beta_h^2\gamma^2(1 + \gamma^2)}}{1 + \gamma^2}.\quad (18)$$

Plug y into Eq. (13) and we obtain the thermal efficiency at maximum power

$$\begin{aligned}\eta_m &= 1 - \frac{1}{\gamma^2}\frac{y}{x} \\ &= 1 - \frac{\gamma^2(1 - \eta_c) - 1 + \sqrt{(1 + \gamma^2)[1 + \gamma^2(1 - \eta_c)^2]}}{(2 - \eta_c)\gamma^2},\end{aligned}\quad (19)$$

where $\eta_c = 1 - \frac{T_c}{T_h}$ is the Carnot efficiency. If we let γ approach 0 and ∞ , respectively, we obtain the upper and lower bounds of η_m as

$$\frac{\eta_c}{2} \leq \eta_m \leq \frac{\eta_c}{2 - \eta_c}.\quad (20)$$

Interestingly, these bounds agree exactly with those given in Ref. [4] for classical thermal engines in the long contact time limit. However, the situation is a little different for our model of quantum thermal engine. The quantum engine, either quantum-well type or harmonic-oscillator type, must expand to perform work after absorbing heat at a hot reservoir. Hence its size must increase afterwards. For a quantum-well-type engine, its width L will increase, while for a harmonic-oscillator-type engine, its spring constant k will decrease. Since the frequency is antiproportional to L^2 or proportional to \sqrt{k} , then $\gamma = \nu_h/\nu_c$ must be larger than 1, or the lower limit of γ is 1 rather than 0. Now we have tighter bounds for η_m

$$\frac{2 - \sqrt{4 - 4\eta_c + 2\eta_c^2}}{2 - \eta_c} \leq \eta_m \leq \frac{\eta_c}{2 - \eta_c}.\quad (21)$$

The efficiency η_m can be expanded in a series of η_c as

$$\eta_m = \frac{1}{2}\eta_c + \frac{\gamma^2}{4(1 + \gamma^2)}\eta_c^2 + O(\eta_c^3).\quad (22)$$

The coefficient of the second-order term lies between 1/8 and 1/4.

C. Efficiency and its bounds in the short contact time limit

In the short time limit such that $\tau \ll 1/a$, the inverse temperature can be approximated to the second order of $a\tau$ as

$$\beta(\tau) \approx \beta_1 + (\beta_2 - \beta_1)a\tau + (\beta_1 - \beta_2)\frac{1}{2}a^2\tau^2. \quad (23)$$

Implementing this approximation, the entropy transfers during the two stages are given by

$$\begin{aligned} \Delta S_h &= v_h^2 \left[-2\beta_{h0}(\beta_h - \beta_{h0})a_h\tau_h \right. \\ &\quad \left. - (\beta_{h0} - \beta_h)(2\beta_{h0} - \beta_h)a_h^2\tau_h^2 \right], \\ \Delta S_c &= v_c^2 \left[-2\beta_{c0}(\beta_c - \beta_{c0})a_c\tau_c \right. \\ &\quad \left. - (\beta_{c0} - \beta_c)(2\beta_{c0} - \beta_c)a_c^2\tau_c^2 \right]. \end{aligned} \quad (24)$$

Using the same convention as in the last section, the constraint $\Delta S_h + \Delta S_c = 0$ gives an equation for x and y . Since $a_{h,c}\tau_{h,c}$ is an infinitesimal quantity, we match both sides of the equation order by order of $a_{h,c}\tau_{h,c}$. To the first and second orders, we get

$$\begin{aligned} \gamma^2(\beta_h + x)x \frac{A_h}{\beta_h v_h} \tau_h &= (\beta_c - y)y \frac{A_c}{\beta_c v_c} \tau_c, \\ \gamma^2 x(\beta_h + 2x)a_h^2\tau_h^2 &= (\beta_c - 2y)ya_c^2\tau_c^2, \end{aligned} \quad (25)$$

from which one can deduce

$$\frac{\beta_h + 2x}{x(\beta_h + x)^2} = \gamma^2 \frac{\beta_c - 2y}{y(\beta_c - y)^2}. \quad (26)$$

The key step here is to simplify the above equation and get a relatively simple relation between x and y as in Ref. [7], hence we can avoid messing up the physics by the mathematical complexity. We assume that the temperature difference is small relative to the temperature of the heat reservoir at each heat transferring stage. Thus, x is small relative to β_h and y small to β_c . Expanding both sides of Eq. (26) to the third order of x and y , we can derive a very simple relation between x and y

$$\frac{y}{x} = \gamma^2 \frac{\beta_h}{\beta_c}. \quad (27)$$

The heat transfers during the two heating and cooling stages are given by

$$\Delta Q_h = \frac{1}{4}N_0h^2v_h^2xa_h\tau_h, \quad \Delta Q_c = -\frac{1}{4}N_0h^2v_c^2ya_c\tau_c, \quad (28)$$

from which the output power is given by

$$P = \frac{1}{4}N_0h^2 \frac{v_h^2xa_h\tau_h - v_c^2ya_c\tau_c}{\tau_h + \tau_c}. \quad (29)$$

Taking into account that the spontaneous emission coefficient A satisfies $A \propto v^2$, except a constant the output power is evaluated as

$$P \propto \frac{(\beta_c - \gamma^2x\beta_h/\beta_c - \beta_h - x)x}{\beta_c - \gamma^2x\beta_h/\beta_c + \gamma(\beta_h + x)\beta_c^2/\beta_h^2}. \quad (30)$$

Solve the equation $\partial P/\partial x = 0$, and plug the only meaningful solution for x into the expression of the efficiency at maximum power

$$\eta_m = 1 - \frac{\beta_h + x}{\beta_c - \gamma^2x\beta_h/\beta_c}. \quad (31)$$

In a series of η_c, η_m can be expanded as

$$\eta_m = \frac{\eta_c}{2} + \frac{\gamma(2\gamma^2 + \gamma + 1)}{8(1 + \gamma + \gamma^2 + \gamma^3)}\eta_c^2 + O(\eta_c^3). \quad (32)$$

Taking $\gamma = 0, \infty$, the bounds of η_m are derived as

$$\frac{\eta_c}{2} \leq \eta_m \leq \frac{\eta_c}{2 - \eta_c}. \quad (33)$$

Interestingly, we obtain the same rough bounds of η_m as in the long time contact limit. Again noting that γ cannot be smaller than 1, the finer bounds of η_m are found to be

$$1 - \sqrt{1 - \eta_c} \leq \eta_m \leq \frac{\eta_c}{2 - \eta_c}. \quad (34)$$

The coefficient of the second-order term of η_m also lies between 1/8 and 1/4.

III. QUANTUM EINSTEIN ENGINE ASSOCIATED WITH THE FD DISTRIBUTION

In this section, we consider the case that the constituent particles of the working substance obey the FD distribution. In fact we will see that this situation will reduce to that associated with the MB distribution even when $\beta E_{1,2} \ll 1$ (if $\beta E_{1,2} \gg 1$, both the FD and BE distributions reduce to the MB distribution). Here we still adopt the same convention for the parameters as in the last section. For each level of the quantum system, the particle numbers of the initial state are given by

$$N_1(0) = \frac{N_0}{1 + \frac{e^{\beta_1 E_1 + 1}}{e^{\beta_1 E_2 + 1}}}, \quad N_2(0) = \frac{N_0}{1 + \frac{e^{\beta_1 E_2 + 1}}{e^{\beta_1 E_1 + 1}}}. \quad (35)$$

Similar to what we have done in the last section, the distribution function $f^F(\beta) = 1/(1 + \frac{e^{\beta E_2 + 1}}{e^{\beta E_1 + 1}})$ is introduced. Thus the initial number distributions are $N_1(0) = N_0[1 - f^F(\beta_1)]$ and $N_2(0) = N_0 f^F(\beta_1)$. When the quantum system is in contact with the hot (cold) reservoir, the heating (cooling) process is described by Einstein's theory of radiation Eq. (2). Solving this equation, we get $N_1(t) = N_0\{1 - f^F[\beta(t)]\}$ and $N_2(t) = N_0 f^F[\beta(t)]$ in which $f^F[\beta(t)]$ is also expressed by Eq. (5) with $\beta(0) = \beta_1$ and $\beta(\infty) = \beta_2$. Hence the heat absorbed by the working substance at time t is $\Delta Q(t) = N_0 h\nu \{f^F[\beta(t)] - f^F[\beta(0)]\}$. To the leading order of $\beta h\nu$ we have

$$f^F(\beta) \approx \frac{1}{2} - \frac{1}{8}\beta h\nu, \quad a^F = \frac{e^{\beta_2 E_2} + e^{\beta_2 E_1} + 2}{e^{\beta_2 E_2} - e^{\beta_2 E_1}} \approx \frac{4A}{\beta_2 h\nu}. \quad (36)$$

The quantum entropy of the working substance is approximated by

$$S^F \approx \ln 2 - \frac{1}{32}\beta^2 h^2 v^2. \quad (37)$$

One can see that the expressions of $f^F(\beta)$, a^F , and S^F differ from their Maxwellian counterparts only in the coefficients of the leading order of $\beta h\nu$. If we go on carrying the calculations as before, it is not difficult to find that the results are the same as those associated with MB distribution. In other words, the quantum Einstein engine with fermionic working substance has no significant difference from that with the Maxwellian working substance if $\beta E_{1,2} \ll 1$.

IV. QUANTUM EINSTEIN ENGINE ASSOCIATED WITH THE BE DISTRIBUTION

A. General results for heat and entropy transfers

Now we consider the the quantum Einstein engine of which the working substance obeys the BE distribution. The discussions follow quite similar steps as the previous section. The initial particle distributions of the two-level quantum systems are

$$N_1(0) = \frac{N_0}{1 + \frac{e^{\beta_1 E_1 - 1}}{e^{\beta_1 E_2 - 1}}}, \quad N_2(0) = \frac{N_0}{1 + \frac{e^{\beta_1 E_2 - 1}}{e^{\beta_1 E_1 - 1}}}. \quad (38)$$

The heating (cooling) process is again governed by Einstein's theory of radiation. Introducing the distribution function $f^B(\beta) = 1/(1 + \frac{e^{\beta E_2 - 1}}{e^{\beta E_1 - 1}})$, then at time t the particle distributions become $N_1(t) = N_0\{1 - f^B[\beta(t)]\}$ and $N_2(t) = N_0 f^B[\beta(t)]$ with $\beta(0) = \beta_1$ and $\beta(\infty) = \beta_2$. The heat transfer is given by $\Delta Q(t) = N_0 h \nu \{f^B[\beta(t)] - f^B[\beta(0)]\}$. Similarly, to the leading order of $\beta h \nu$ we have

$$f^B(\beta) \approx \frac{E_1}{E_1 + E_2} - \frac{1}{2} \frac{h \nu \beta E_1 E_2}{(E_1 + E_2)^2}, \quad (39)$$

$$a^B = \frac{e^{\beta_2 E_2} + e^{\beta_2 E_1} - 2}{e^{\beta_2 E_2} - e^{\beta_2 E_1}} \approx \frac{A(E_1 + E_2)}{h \nu}.$$

The quantum entropy transfer is further approximated by

$$S^B \approx - \left[\frac{E_1}{E_1 + E_2} \ln \frac{E_1}{E_1 + E_2} + \frac{E_2}{E_1 + E_2} \ln \frac{E_2}{E_1 + E_2} \right] - \frac{E_1 E_2 \ln \frac{E_2}{E_1} h \nu}{2(E_1 + E_2)^2} \beta$$

$$- \frac{E_1 E_2 h \nu (3(E_2^2 - E_1^2) + 2(E_1^2 - 4E_1 E_2 + E_2^2) \ln \frac{E_1}{E_2})}{24(E_1 + E_2)^3} \beta^2. \quad (40)$$

In what follows, we will ignore the superscript “ B ” for simplicity. For the heating stage, we use E_{h0} and E_h to denote the initial (low) and final (high) energy levels, β_{h0} and $\beta_h(t)$ to denote the initial and final inverse temperatures. Define the frequency ν_h by $E_h - E_{h0} = h \nu_h$, then the heat and entropy transfers during the heating and cooling stages are given by

$$\Delta Q_h(t) = \frac{1}{2} N_0 h^2 \nu_h^2 X_h [\beta_{h0} - \beta_h(t)], \quad \Delta S_h(t) = Y_{h1} [\beta_{h0} - \beta_h(t)] + Y_{h2} [\beta_{h0}^2 - \beta_h^2(t)], \quad (41)$$

$$\Delta Q_c(t) = \frac{1}{2} N_0 h^2 \nu_c^2 X_c [\beta_{c0} - \beta_c(t)], \quad (42)$$

$$\Delta S_c(t) = Y_{c1} [\beta_{c0} - \beta_c(t)] + Y_{c2} [\beta_{c0}^2 - \beta_c^2(t)], \quad (43)$$

where

$$X_h = \frac{E_{h0} E_h}{(E_{h0} + E_h)^2}, \quad Y_{h1} = \frac{E_h E_{h0} \ln \frac{E_h}{E_{h0}} h \nu_h}{2(E_h + E_{h0})^2}, \quad Y_{h2} = \frac{E_{h0} E_h h \nu_h (3(E_h^2 - E_{h0}^2) + 2(E_{h0}^2 - 4E_{h0} E_h + E_h^2) \ln \frac{E_{h0}}{E_h})}{24(E_{h0} + E_h)^3},$$

$$X_c = \frac{E_{c0} E_c}{(E_{c0} + E_c)^2}, \quad Y_{c1} = \frac{E_c E_{c0} \ln \frac{E_c}{E_{c0}} h \nu_c}{2(E_c + E_{c0})^2}, \quad Y_{c2} = \frac{E_{c0} E_c h \nu_c (3(E_c^2 - E_{c0}^2) + 2(E_{c0}^2 - 4E_{c0} E_c + E_c^2) \ln \frac{E_{c0}}{E_c})}{24(E_{c0} + E_c)^3}.$$

B. Efficiency and its bounds in the long contact time limit

From now on, the discussions are simply parallel to what we have done in the last section. We briefly outline our results here. In this limit $\tau_{h,c} \rightarrow \infty$. As previously, we assume $\beta_h(\tau_h) = \beta_h$, $\beta_c(\tau_c) = \beta_c$, $\beta_{h0} - \beta_h = x$ and $\beta_{c0} - \beta_c = -y$. From $\Delta S_h + \Delta S_c = 0$ we have

$$Y_{h1} x + Y_{h2} (2\beta_h + x)x - Y_{c1} y - Y_{c2} (2\beta_c - y)y = 0. \quad (44)$$

Solving this equation, we have

$$x = \sqrt{\beta_h'^2 + \frac{1}{\gamma_1^2} (2\beta_c' - y)y} - \beta_h', \quad (45)$$

$$\beta_h' = \beta_h + \frac{Y_{h1}}{2Y_{h2}}, \quad \beta_c' = \beta_c + \frac{Y_{c1}}{2Y_{c2}}, \quad \gamma_1^2 = \frac{Y_{h2}}{Y_{c2}}. \quad (46)$$

The power of this heat engine is given by

$$P = \frac{1}{2} N_0 h^2 \frac{X_h \nu_h^2 x - X_c \nu_c^2 y}{\tau_h + \tau_c}. \quad (47)$$

It is maximized when $\partial P / \partial y = 0$. Let $\gamma_2^2 = \frac{X_h \nu_h^2}{X_c \nu_c^2}$, then we have $\frac{\partial x}{\partial y} - \frac{1}{\gamma_2^2} = 0$. Using Eq. (45), the only meaningful solution for y is

$$y = \frac{\beta_c' (\gamma_1^2 + \gamma_2^4) - \sqrt{(\beta_c'^2 \gamma_1^2 + \beta_h'^2 \gamma_1^4) (\gamma_1^2 + \gamma_2^4)}}{\gamma_1^2 + \gamma_2^4}. \quad (48)$$

The efficiency of the thermal engine at maxim power is

$$\eta_m = 1 - \frac{X_c \nu_c^2 y}{X_h \nu_h^2 x} = 1 - \frac{1}{\gamma_2^2} \frac{y}{x}. \quad (49)$$

Plugging in Eqs. (45) and (48) we have

$$\eta_m = 1 - \frac{\gamma_1^2}{\gamma_2^2} \times \frac{\gamma_2^2 (1 - \eta_c') - 1 + \frac{1}{\gamma_1} \sqrt{[1 + \gamma_1^2 (1 - \eta_c')^2] (\gamma_1^2 + \gamma_2^4)}}{\gamma_2^2 + \gamma_1^2 (1 - \eta_c')}, \quad (50)$$

where $\eta'_c = 1 - \frac{\beta'_h}{\beta'_c}$ can be thought of as the corrected Carnot efficiency. If we chose suitable $E_{h,c}$ and $E_{h0,c0}$ such that $\gamma_1 = \gamma_2 = \gamma'$, Eq. (50) “recovers” the result (19) except that η_c is replaced by η'_c and γ by γ' . By inspecting the numerators and denominators of γ_1 and γ_2 , one can find that they are of the same order of $E_{h,c}$ and $E_{h0,c0}$, respectively. Hence it is reasonable to assume that they are of the same order when approaching 0 or ∞ . Therefore we get a rough estimate of the upper and lower bounds

$$\frac{\eta'_c}{2} \leq \eta_m \leq \frac{\eta'_c}{2 - \eta'_c}. \quad (51)$$

Following the same reasoning as before, the tighter bounds of η_m are given by

$$\frac{2 - \sqrt{4 - 4\eta'_c + 2\eta'^2_c}}{2 - \eta'_c} \leq \eta_m \leq \frac{\eta'_c}{2 - \eta'_c}. \quad (52)$$

Despite the similarity between the results associated with the BE distribution and those associated with the MB and FD distributions, there is also a qualitative difference between them. Obviously the latter only depend on the difference of energy levels, or $v_{h,c}$. However, the former has an explicit dependence on the choice of initial (low) energy level $E_{h0,c0}$.

C. Efficiency and its bounds in the short contact time limit

We consider the limit that $\tau \ll 1/a$ and expand the inverse temperature to the second order of $a\tau$, then the entropy transfers during the two stages are given by

$$\begin{aligned} \Delta S_h &= -2Y_{h2}(\beta'_h + x)xa_h\tau_h - Y_{h2}(\beta'_h + 2x)xa_h^2\tau_h^2, \\ \Delta S_c &= 2Y_{c2}(\beta'_c - y)ya_c\tau_c + Y_{c2}(\beta'_c - 2y)ya_c^2\tau_c^2. \end{aligned} \quad (53)$$

While the heat transfers are

$$\Delta Q_h = \frac{1}{2}N_0h^2v_h^2X_hxa_h\tau_h, \quad \Delta Q_c = -\frac{1}{2}N_0h^2v_c^2X_cya_c\tau_c. \quad (54)$$

As before we match both sides of $\Delta S_h + \Delta S_c = 0$ order by order of $a\tau$, then the first and second orders of $a\tau$ give

$$\begin{aligned} \gamma_1^2(\beta'_h + x)xa_h\tau_h &= (\beta'_c - y)ya_c\tau_c, \\ \gamma_1^2(\beta'_h + 2x)xa_h^2\tau_h^2 &= (\beta'_c - 2y)ya_c^2\tau_c^2, \end{aligned} \quad (55)$$

from which we deduce

$$\frac{\beta'_h + 2x}{x(\beta'_h + x)^2} = \gamma_1^2 \frac{\beta'_c - 2y}{y(\beta'_c - y)^2}. \quad (56)$$

Using the same argument as in the last section, one can find

$$\frac{y}{x} = \gamma_1^2 \frac{\beta'_h}{\beta'_c}. \quad (57)$$

The spontaneous emission coefficient A satisfies $A \propto v^2$, then the output power is evaluated as

$$P = \frac{1}{2}N_0h^2v_h^2X_ha_h \frac{(\beta'_c - \gamma_1^2x\beta'_h/\beta'_c - \frac{\gamma_1^2}{\gamma_2^2}(\beta'_h + x))x}{\beta'_c - \gamma_1^2x\beta'_h/\beta'_c + \gamma_3(\beta'_h + x)\beta'_c/\beta'_h}, \quad (58)$$

where $\gamma_3 = \frac{v_h(E_{h0}+E_h)}{v_c(E_{c0}+E_c)}$. The power is maximized when $\partial P/\partial x = 0$, which leads to the solution of the efficiency at maximum power is

$$\eta_m = \frac{\beta'_h\gamma_1^2 + \beta'_c\gamma_2^2\gamma_3 - \gamma_1\sqrt{\frac{\beta'_c\beta'_h(\beta'_c+\beta'_h\gamma_2^2)(1+\gamma_3)(\beta'_h\gamma_1^2+\beta'_c\gamma_2^2\gamma_3)}{\beta_c^2+\beta_h^2\gamma_1^2}}}{\gamma_2^2\left[\beta'_c\gamma_3 - \beta'_h\gamma_1\sqrt{\frac{\beta'_c\beta'_h(1+\gamma_3)(\beta'_h\gamma_1^2+\beta'_c\gamma_2^2\gamma_3)}{(\beta_c^2+\beta_h^2\gamma_1^2)(\beta'_c+\beta'_h\gamma_2^2)}}\right]}. \quad (59)$$

If $E_{h,c}$ and $E_{h0,c0}$ are chosen suitably such that $\gamma_1 = \gamma_2 = \gamma_3 = \gamma'$, the efficiency η_m can also be expanded in a series of η'_c as

$$\eta_m = \frac{\eta'_c}{2} + \frac{\gamma'(2\gamma'^2 + \gamma' + 1)}{8(1 + \gamma' + \gamma'^2 + \gamma'^3)}\eta_c^2 + O(\eta_c^3). \quad (60)$$

Interestingly, this also “recovers” the result (32) expect that η_c is replaced by η'_c and γ by γ' . Similarly, when γ' approaches 0, ∞ or 1, ∞ , the rough and fine bounds of η_m are found to be

$$\frac{\eta'_c}{2} \leq \eta_m \leq \frac{\eta'_c}{2 - \eta'_c}, \quad 1 - \sqrt{1 - \eta'_c} \leq \eta_m \leq \frac{\eta'_c}{2 - \eta'_c}. \quad (61)$$

V. CONCLUSION

In conclusion, we present an analysis of the quantum thermal engine of which the heat transferring law is derived from Einstein’s theory of radiation. We notice that heat transferring laws play a crucial role on the problems about the efficiency of quantum thermal engines at maximum power. The thermal efficiency and its bounds at maximum power for quantum Einstein engines are studied in the long and short time limits. To some extent, this can be thought of as the quantum counterpart of the classical thermal engine studied in Ref. [7], which can simulate some well-known classical thermal engines. For $\beta h v \ll 1$, we find that the quantum Einstein engine with fermionic working substance has no difference from that with the Maxwellian working substance, while the one with bosonic working substance has a qualitative difference.

ACKNOWLEDGMENTS

H.Y. thanks the support by the US Department of Energy, Office of Science under Grant No. DE-FG02-03ER46093. H.G. thanks the support by Natural Science Foundation of Jiangsu Province, China (SBK201241926). H.Y. thanks Professor M. W. Snow for support.

- [1] F. Curzon and B. Ahlborn, *Am. J. Phys.* **43**, 22 (1975).
 [2] P. Salamon and A. Nitzan, *J. Chem. Phys.* **74**, 3546 (1981).
 [3] M. J. Ondrechen, M. H. Rubin, and Y. B. Band, *J. Chem. Phys.* **78**, 4721 (1983).

- [4] M. Esposito, R. Kawai, K. Lindenberg, and C. Van den Broeck, *Phys. Rev. Lett.* **105**, 150603 (2010).
 [5] M. Esposito, K. Lindenberg, and C. Van den Broeck, *Phys. Rev. Lett.* **102**, 130602 (2009).

- [6] C. Van den Broeck, *Phys. Rev. Lett.* **95**, 190602 (2005).
- [7] H. Yan and H. Guo, *Phys. Rev. E* **85**, 011146 (2012).
- [8] H. T. Quan, Y. X. Liu, C. P. Sun, and F. Nori, *Phys. Rev. E* **76**, 031105 (2007).
- [9] H. T. Quan, *Phys. Rev. E* **79**, 041129 (2009).
- [10] Y. Lu and G. L. Long, *Phys. Rev. E* **85**, 011125 (2012).
- [11] J. Chen, B. Lin, and B. Hua, *J. Phys. D: Appl. Phys.* **35**, 2051 (2002).
- [12] B. Lin and J. Chen, *J. Phys. A: Math. Gen.* **38**, 69 (2005).
- [13] S. Abe, *Phys. Rev. E* **83**, 041117 (2011).
- [14] C. M. Bender, D. C. Brody, and B. K. Meister, *J. Phys. A* **33**, 4427 (2000).
- [15] O. Abah, J. Rossnagel, G. Jacob, S. Deffner, F. Schmidt-Kaler, K. Singer, and E. Lutz, arXiv:1205.1362.
- [16] E. Hecht and A. R. Ganesan, *Optics* (Pearson, New Delhi, India, 2008).
- [17] B. E. A. Salech and M. C. Teich, *Fundamentals of Photonics* (Wiley & Sons, New York, 2007).