

**Higher-Dimensional Quantum Hypergraph-Product Codes with Finite Rates**

Weilei Zeng\* and Leonid P. Pryadko†

*Department of Physics and Astronomy, University of California, Riverside, California 92521, USA*

(Received 8 October 2018; published 11 June 2019)

We describe a family of quantum error-correcting codes which generalize both the quantum hypergraph-product codes by Tillich and Zémor and all families of toric codes on  $m$ -dimensional hypercubic lattices. Parameters of the constructed codes, including the minimum distances, are given explicitly in terms of those of binary codes associated with the matrices used in the construction.

DOI: [10.1103/PhysRevLett.122.230501](https://doi.org/10.1103/PhysRevLett.122.230501)

Quantum low-density parity-check (q-LDPC) codes are the only class of codes known to combine finite rates with nonzero fault-tolerant (FT) thresholds [1,2], and to allow scalable quantum computation with a finite multiplicative overhead [3]. However, unlike in the classical case, where capacity-approaching codes can be constructed from random sparse matrices [4–7], matrices suitable for constructing quantum LDPC codes are highly atypical in the corresponding ensembles. Thus, an algebraic ansatz is required to construct large-distance q-LDPC codes. Precious few examples of algebraic constructions are known that give finite rate codes and also satisfy conditions [2] for fault-tolerance: bounded weight of stabilizer generators and minimum distance that scales logarithmically or faster with the block length  $n$ . Such constructions include hyperbolic codes on two- and higher-dimensional manifolds [8–12], and quantum hypergraph-product (QHP) and related codes [13–15]. Further, some constructions, e.g., in Refs. [16–20], have finite rates and relatively high distances, with the stabilizer generator weights that grow with  $n$  logarithmically. It is not known whether these codes have nonzero FT thresholds. However, such codes can be modified into those with provable FT thresholds with the help of weight reduction [21].

There is more variety for topological codes, which can be viewed as generalizations of the toric code [22–28] invented by Kitaev [29]. Such a code can be constructed from any tessellation of an arbitrary surface or a higher-dimensional manifold. The essential advantage of topological codes is locality: each stabilizer generator involves only the qubits in the immediate vicinity of each other; this makes planar surface codes so practically attractive. However, locality also limits the parameters of topological codes [30–33]. In particular, for a code of length  $n$  with generators local in two dimensions, the number of encoded qubits  $k$  and the minimal distance  $d$  satisfy the inequality [30]  $kd^2 \leq \mathcal{O}(n)$ . This implies asymptotically zero rate,  $k/n \rightarrow 0$ , whenever  $d$  diverges with  $n$ .

In this work we construct a family of q-LDPC codes that generalize the QHP codes [13,14] to higher dimensions,

and explicitly calculate their parameters, including the minimum distances. Our codes relate to toric codes on hypercubic lattices [24–28] in exactly the same fashion as the QHP codes relate to the square-lattice toric code. Just as different  $m$ -dimensional toric codes on a hypercubic lattice are parts of an  $m$  complex [25], here we also construct  $m$  complexes, chain complexes with  $m$  nontrivial boundary operators. Our construction is recursive: it defines an  $m$ -complex  $\mathcal{K}_m$  as a tensor product of a shorter chain complex  $\mathcal{K}_{m-1}$  and a 1-complex  $\mathcal{K}_1$ , a linear map between two binary vector spaces. In particular, the construction of the 2-complex  $\mathcal{K}_2$  in terms of two binary matrices is identical to QHP codes [13,14].

Previously, related constructions have been considered in Refs. [19,21,34]. Hastings [21] only considered products with 1-complexes that correspond to classical repetition codes, in essence, the same construction that appears in “space-time” codes used in the analysis of repeated syndrome measurement [1,2,35,36]. On the other hand, Audoux and Couvreur [19] and Campbell [34] only considered products of 2-complexes. Their lower bounds on code distances are not as strong as ours.

In addition to defining new classes of quantum LDPC codes with parameters known explicitly, our construction may be useful for (i) optimizing repeated measurements in the problem of FT quantum error correction [1,2,35,36], (ii) related problem of single-shot error correction [34, 37–39], (iii) analysis of transformations between different QECCs, like the distance-balancing trick by Hastings [21], and (iv) construction of asymmetric quantum CSS codes optimized for operation where error rates for  $X$  and  $Z$  channels may differ strongly [40–45].

We start with a brief overview of error correcting codes and chain complexes; see, e.g., Refs. [19,25,46–50] for much more information. A classical binary linear code  $\mathcal{C}$  with parameters  $[n, k, d]$  is a  $k$ -dimensional subspace of the vector space  $\mathbb{F}_2^n$  of all binary strings of length  $n$ . The code distance  $d$  is the minimal Hamming weight of a nonzero string in the code. A code  $\mathcal{C} \equiv \mathcal{C}_G$  can be specified in terms of the generator matrix  $G$  whose rows are the basis vectors

of the code. All vectors orthogonal to the rows of  $G$  form the dual code  $\mathcal{C}_G^\perp = \{c \in \mathbb{F}_2^n | Gc^T = 0\}$ . The matrix  $G$  is also called the parity check matrix of the code  $\mathcal{C}_G^\perp$ .

Given an *index set*  $I \subseteq \{1, 2, \dots, n\}$  of length  $|I| = r$ , and a string  $c \in \mathbb{F}_2^n$ , let  $c[I] \in \mathbb{F}_2^r$  be a substring of  $c$  with the bits at all positions  $i \notin I$  dropped. Similarly, for an  $n$ -column matrix  $G$  with rows  $g_j$ ,  $G[I]$  is formed by the rows  $g_j[I]$ . If  $\mathcal{C} = \mathcal{C}_G$  is a linear code with the generating matrix  $G$ , the *punctured* code  $\mathcal{C}_p[I] \equiv \{c[I] : c \in \mathcal{C}\}$  is a linear code of length  $|I|$  with the generating matrix  $G[I]$ . The *shortened* code  $\mathcal{C}_s[I]$  is formed similarly, except only from the codewords which have all zero bits outside  $I$ ,  $\mathcal{C}_s[I] = \{c[I] : c = (c_1, c_2, \dots, c_n) \in \mathcal{C} \text{ and } c_i = 0 \text{ for each } i \notin I\}$ . If  $\mathcal{C} = \mathcal{C}_P^\perp$  has the parity check matrix  $P$ ,  $P[I]$  is the parity check matrix of the shortened code  $\mathcal{C}_s[I]$ .

A *chain complex* is a sequence of finite-dimensional vector spaces  $\dots, \mathcal{A}_{j-1}, \mathcal{A}_j, \dots$  with *boundary operators*  $\partial_j : \mathcal{A}_{j-1} \leftarrow \mathcal{A}_j$  that map between each pair of neighboring spaces, with the requirement  $\partial_j \partial_{j+1} = 0$ ,  $j \in \mathbb{Z}$ . In this work we only consider vector spaces  $\mathcal{A}_j = \mathbb{F}_2^{n_j}$  formed by binary vectors of length  $n_j \geq 0$ , and define an  $m$ -complex  $\mathcal{A} \equiv \mathcal{K}(A_1, \dots, A_m)$ , a length- $(m+1)$  chain complex with a basis, in terms of  $n_{j-1} \times n_j$  binary matrices  $A_j$  serving as the boundary operators,

$$\mathcal{A} : \{0\} \xleftarrow{\partial_0} \mathcal{A}_0 \xleftarrow{A_1} \mathcal{A}_1 \dots \xleftarrow{A_m} \mathcal{A}_m \xleftarrow{\partial_{m+1}} \{0\}, \quad (1)$$

where the neighboring matrices must be mutually orthogonal,  $A_{j-1}A_j = 0$ ,  $j \in \{1, \dots, m\}$ . In addition to boundary operators given by the matrices  $A_j$ , implicit are the trivial operators  $\partial_0 : \{0\} \leftarrow \mathcal{A}_0$  and  $\partial_{m+1} : \mathcal{A}_m \leftarrow \{0\}$  treated formally as zero  $0 \times n_0$  and  $n_m \times 0$  matrices.

Elements of the subspace  $\text{Im}(\partial_{j+1}) \subseteq \mathcal{A}_j$  are called *boundaries*; in our case these are linear combinations of columns of  $A_{j+1}$  and, therefore, form a binary linear code with the generator matrix  $A_{j+1}^T$ ,  $\text{Im}(A_{j+1}) = \mathcal{C}_{A_{j+1}^T}$ . In the singular case  $j = m$ ,  $\text{Im}(\partial_{m+1}) = \{0\}$ , a trivial vector space. Elements of  $\text{Ker}(\partial_j) \subset \mathcal{A}_j$  are called *cycles*; in our case these are vectors in a binary linear code with the parity check matrix  $A_j$ ,  $\text{Ker}(A_j) = \mathcal{C}_{A_j}^\perp$ . In the singular case  $j = 0$ ,  $\text{Ker}(\partial_0) = \mathcal{A}_0$ .

Because of the orthogonality  $\partial_j \partial_{j+1} = 0$ , all boundaries are necessarily cycles,  $\text{Im}(\partial_{j+1}) \subseteq \text{Ker}(\partial_j) \subseteq \mathcal{A}_j$ . The structure of the cycles in  $\mathcal{A}_j$  that are not boundaries is described by the  $j$ th homology group,

$$H_j(\mathcal{A}) \equiv H(A_j, A_{j+1}) = \text{Ker}(A_j) / \text{Im}(A_{j+1}). \quad (2)$$

The group quotient here means that two cycles [elements of  $\text{Ker}(A_j)$ ] that differ by a boundary [element of  $\text{Im}(A_{j+1})$ ] are considered equivalent, denoted as  $x \simeq y \in \mathcal{A}_j$ . Explicitly,  $y = x + A_{j+1}\alpha$  for some  $\alpha \in \mathcal{A}_{j+1}$ . Nonzero elements of  $\mathcal{H}_j(\mathcal{A})$  are equivalence classes of homologically nontrivial

cycles. The rank of  $j$ th homology group is the dimension of the corresponding vector space; one has

$$k_j \equiv \text{rank} H_j(\mathcal{A}) = n_j - \text{rank} A_j - \text{rank} A_{j+1}. \quad (3)$$

The homological *distance*  $d_j$  is the minimum Hamming weight of a nontrivial element (any representative) in the homology group  $H_j(\mathcal{A}) \equiv H(A_j, A_{j+1})$ ,

$$d_j = \min_{0 \neq x \in H_j(\mathcal{A})} \text{wgt } x = \min_{x \in \text{Ker}(A_j) \setminus \text{Im}(A_{j+1})} \text{wgt } x. \quad (4)$$

By this definition,  $d_j \geq 1$ . To address singular cases, throughout this work we assume that the minimum of an empty set is an infinity;  $k_j = 0$  always implies  $d_j = \infty$ .

In addition to the homology group  $H(A_j, A_{j+1})$ , there is also a generally distinct *co-homology* group  $\tilde{H}_j(\tilde{\mathcal{A}}) = H(A_{j+1}^T, A_j^T)$  of the same rank (3); this is associated with the *co-chain complex*  $\tilde{\mathcal{A}}$  formed from the transposed matrices  $A_j^T$  taken in the opposite order. A quantum Calderbank-Shor-Steane (CSS) code [51,52] with generator matrices  $G_X = A_j$  and  $G_Z = A_{j+1}^T$  is isomorphic with the direct sum of the groups  $H_j$  and  $\tilde{H}_j$ ,

$$\mathcal{Q}(A_j, A_{j+1}^T) \cong H(A_j, A_{j+1}) \oplus H(A_{j+1}^T, A_j^T). \quad (5)$$

The two terms correspond to  $Z$  and  $X$  logical operators, respectively. The code distance can be expressed as a minimum over the distances  $d_j$  and  $\tilde{d}_j$  of the two homology groups. Parameters of such a code are written as  $[[n_j, k_j, \min(d_j, \tilde{d}_j)]]$ .

The tensor product  $\mathcal{A} \times \mathcal{B}$  of two chain complexes  $\mathcal{A}$  and  $\mathcal{B}$  is defined as the chain complex formed by linear spaces decomposed as direct sums of Kronecker products,

$$(\mathcal{A} \times \mathcal{B})_i = \bigoplus_{i+j=i} \mathcal{A}_i \otimes \mathcal{B}_j, \quad (6)$$

with the action of the boundary operators

$$\partial'''(a \otimes b) \equiv \partial'_i a \otimes b + (-1)^i a \otimes \partial''_j b, \quad (7)$$

where  $a \in \mathcal{A}_i$ ,  $b \in \mathcal{B}_j$ , and the boundary operators  $\partial'_i$ ,  $\partial''_j$ , and  $\partial'''$  act in complexes  $\mathcal{A}$ ,  $\mathcal{B}$ , and  $\mathcal{A} \times \mathcal{B}$ , respectively. When both  $\mathcal{A}$  and  $\mathcal{B}$  are *bounded*, that is, they include finite numbers of nontrivial spaces, the dimension  $n_j(\mathcal{C})$  of a space  $\mathcal{C}_j$  in the product  $\mathcal{C} = \mathcal{A} \times \mathcal{B}$  is

$$n_j(\mathcal{C}) = \sum_i n_i(\mathcal{A}) n_{j-i}(\mathcal{B}). \quad (8)$$

The homology groups of the product  $\mathcal{C} = \mathcal{A} \times \mathcal{B}$  are isomorphic to a simple expansion in terms of those of  $\mathcal{A}$  and  $\mathcal{B}$ , which is given by the Künneth theorem,

$$H_j(\mathcal{C}) \cong \bigoplus_i H_i(\mathcal{A}) \otimes H_{j-i}(\mathcal{B}). \quad (9)$$

One immediate consequence is that the rank  $k_j(\mathcal{C})$  of the  $j$ th homology group  $H_j(\mathcal{C})$  is

$$k_j(\mathcal{C}) = \sum_i k_i(\mathcal{A})k_{j-i}(\mathcal{B}). \quad (10)$$

Our first result is an upper bound on the distances of the homological groups in a chain complex  $\mathcal{A} \times \mathcal{B}$ , an immediate extension of Cor. 2.14 from Ref. [19],

$$d_j(\mathcal{C}) \leq \min_i d_i(\mathcal{A})d_{j-i}(\mathcal{B}). \quad (11)$$

*Proof of Eq. (11).*—This is a consequence of a version of the Künneth theorem for a pair of chain complexes with chosen bases, see Proposition 1.13 in Ref. [19]. Namely, if, for each  $r \in \mathbb{Z}$ , the sets  $X_r \subset \mathcal{A}_r$  and  $Y_r \subset \mathcal{B}_r$  induce bases for  $H_r(\mathcal{A})$  and  $H_r(\mathcal{B})$ , respectively, then, for every  $j \in \mathbb{Z}$ , the vectors in the set

$$Z_j = \{x \otimes y | i \in \mathbb{Z}, x \in X_i, y \in Y_{j-i}\} \quad (12)$$

induce a basis for  $H_j(\mathcal{A} \otimes \mathcal{B})$ . Now, if we choose each of the sets  $X_r$  and  $Y_r$  to contain the corresponding minimum-weight vectors, minimum weight of the elements of the set (12) equals to the right-hand side in Eq. (11). The homology group is trivial,  $k_j(\mathcal{A} \otimes \mathcal{B}) = 0$  and  $Z_j = \emptyset$ , only if at least one of the sets in each pair  $\{a_i, b_{j-i}\}$ ,  $i \in \mathbb{Z}$  is empty, which implies that the corresponding product  $d_i(\mathcal{A})d_{j-i}(\mathcal{B})$  be infinite, consistent with the result given by our convention,  $d_j(\mathcal{C}) = \infty$  whenever  $k_j(\mathcal{C}) = 0$ .  $\square$

Our second result is a lower bound on the distance for the special case where  $\mathcal{B} = \mathcal{K}(P)$  is a 1-complex induced by an  $r \times c$  binary matrix  $P$ . This bound matches the upper bound in Eq. (11), and thus ensures the equality for the case where  $\mathcal{B}$  is a 1-complex. This expression,

$$d_j(\mathcal{A} \times \mathcal{B}) = \min(d_j(\mathcal{A})d_0(\mathcal{B}), d_{j-1}(\mathcal{A})d_1(\mathcal{B}), \dots), \quad (13)$$

where  $\mathcal{B} = \mathcal{K}(P)$  is a 1-complex, is our main result.

With  $\mathcal{A}$  the  $m$  complex in Eq. (1), the tensor product  $\mathcal{C} \equiv \mathcal{A} \times \mathcal{B}$  can be written as an  $(m+1)$  complex,  $\mathcal{C} = \mathcal{K}(C_1, \dots, C_{m+1})$ , with the block matrices

$$C_{j+1} = \left( \begin{array}{c|c} A_{j+1} \otimes E_r & (-1)^j E_{n_i} \otimes P \\ \hline & A_j \otimes E_c \end{array} \right), \quad (14)$$

where  $E_r$  denotes the  $r \times r$  identity matrix. The sign in the top-right corner ensures orthogonality  $C_j C_{j+1} = 0$ ; in our case spaces are binary and signs have no effect. We also notice that since  $\partial_0$  and  $\partial_{m+1}$  in  $\mathcal{A}$  are both trivial, matrices  $C_1$  and  $C_{m+1}$ , respectively, will be missing the lower and the left block pairs. If we denote  $u \equiv \text{rank } P$ , the two

homology groups associated with  $\mathcal{B}$  have ranks  $\kappa_0 \equiv k_0(\mathcal{B}) = r - u$  and  $\kappa_1 \equiv k_1(\mathcal{B}) = c - u$ , respectively. Equations (8) and (10) give in this case,

$$n'_j = n_j r + n_{j-1} c \quad \text{and} \quad k'_j = k_j \kappa_0 + k_{j-1} \kappa_1, \quad (15)$$

where we use the primes to denote the parameters of  $\mathcal{C}$ ,  $n'_j \equiv n_j(\mathcal{C})$  and  $k'_j \equiv k_j(\mathcal{C})$ . We now prove the claimed lower bound for the distance [53]:

**Theorem 1.** Consider  $m$ -complex  $\mathcal{A}$  in Eq. (1), and assume that homological groups  $H_j(\mathcal{A})$  have distances  $d_j$ ,  $0 \leq j \leq m$ . Given an  $r \times c$  binary matrix  $P$  of rank  $u$ , construct matrices  $C_j$  in Eq. (14). Denote  $\delta$  the minimum distance of a binary code with the parity check matrix  $P$ ; by our convention,  $\delta = \infty$  if  $u = c$ . The minimum distance  $d'_j \equiv d_j(\mathcal{C})$  of the homology group  $H(C_j, C_{j+1})$ ,  $0 \leq j \leq m+1$ , satisfies the following lower bounds: (i) if  $r > u$ ,  $d'_j \geq \min(d_j, d_{j-1}\delta)$ , otherwise, (ii) if  $r = u$ ,  $d'_j \geq d_{j-1}\delta$ .

We notice that in Eq. (13),  $d_j(\mathcal{A}) \equiv d_j$ ,  $d_1(\mathcal{B}) = \delta$ , while  $d_0(\mathcal{B}) = 1$  in case (i) and it is infinite in case (ii).

*Proof of Theorem 1.*—Start with (i). Take a block vector  $e = (e_1 | e_2)$ , with  $e_1 \in \mathbb{F}_2^{n_j r}$ ,  $e_2 \in \mathbb{F}_2^{n_j c}$ , with component weights  $w_1 \equiv \text{wgt}(e_1) < d_j$ , and  $w_2 \equiv \text{wgt}(e_2) < d_{j-1}\delta$ , and assume  $C_j e^T = 0$ . We are going to show that  $e$  is a linear combination of columns of  $C_{j+1}$ .

Step 1: This step is needed if  $d_j$  is finite; otherwise let  $C'_j = C_j$ ,  $C'_{j+1} = C_{j+1}$ ,  $e' = e$ , and proceed to step 2. Mark the columns in  $A_j$  which are incident on nonzero positions in  $e_1$ . That is, write

$$e_1 = \sum_{i=1}^r a_i \otimes x_i,$$

where  $a_i \in \mathbb{F}_2^{n_j}$ , and  $x_i \in \mathbb{F}_2^r$  with the only nonzero bit at position  $i$ . Take  $I_0$  the union of the supports of all vectors  $a_i$ . Denote the corresponding submatrix of  $A_j$  as  $A_j^{(0)} = A_j[I_0]$ ; this is the generating matrix of a code  $\mathcal{C}_{A_j}$  punctured at the positions not in  $I_0$ . Further, denote  $A_{j+1}^{(0)}$  a transposed generating matrix of the code  $\mathcal{C}_{A_{j+1}^T}$  shortened to  $I_0$ ; it is obtained from a linear combination of columns of  $A_{j+1}$  by dropping rows not in  $I_0$ .

By construction,  $n_j^{(0)} \equiv |I_0| \leq w_1$ ; since  $w_1 < d_j$ , the homology group  $H(A_j^{(0)}, A_{j+1}^{(0)})$  is trivial. Now, increase  $I_0$  by adding indices of all linearly independent columns of  $A_j$  to get  $I_1 \supseteq I_0$  and  $A'_j = A_j[I_1]$ , such that  $|I_1| - |I_0| = \text{rank}(A'_j) - \text{rank}(A_j^{(0)})$  and in addition  $\text{rank}(A'_j) = \text{rank}(A_j)$ . Similarly, denote  $A'_{j+1}$  a transposed generating matrix of the code  $\mathcal{C}_{A'_{j+1}^T}$  shortened to  $I_1$ ; it satisfies  $\text{rank}(A'_{j+1}) = \text{rank}(A_{j+1}^{(0)})$ . Then  $H(A'_j, A'_{j+1})$  still has zero rank, and

$H(A_{j-1}, A_j) = H(A_{j-1}, A'_j)$ . Use Eq. (14) to construct the corresponding matrices  $C'_j$  and  $C'_{j+1}$  and define the punctured vectors  $e'_1 = \sum_i a_i [I_1] \otimes x_i$ ,  $e' = (e'_1 | e_2)$ . Since we only removed zero positions, the new vector satisfies  $C'_j (e')^T = 0$ . Also, if there exists a vector  $\alpha' \in C'_{j+1}$  such that  $(e')^T = C'_{j+1}(\alpha')^T$ , then necessarily  $e^T = C_{j+1}\alpha^T$  with some  $\alpha \in C_{j+1}$ .

Step 2: Consider the decomposition

$$e_2 = \sum_{\ell=1}^c f_\ell \otimes y_\ell, \quad f_\ell \in \mathbb{F}_2^{n_{j-1}}, \quad (16)$$

where  $y_\ell \in \mathbb{F}_2^c$  has the only nonzero bit at  $\ell$ . The identity  $C'_j (e')^T = 0$  implies  $A_{j-1} f_\ell^T = 0$  for any  $1 \leq \ell \leq c$ . For those  $\ell$  where  $f_\ell^T$  is linearly dependent with the columns of  $A'_j$ ,  $f_\ell^T = A'_j \alpha_\ell^T$  with some  $\alpha_\ell \in C'_j = \mathbb{F}_2^{n'_j}$ , render this vector to zero by the equivalence transformation

$$(e')^T \rightarrow (e')^T + C'_{j+1}(0 | \alpha_\ell \otimes y_\ell)^T.$$

Such a transformation only affects one vector  $f_\ell$ . It may also modify the first block of  $e'$ , which is of no importance since  $H(A'_j, A'_{j+1})$  is trivial. The resulting vector  $\bar{e}' = (\bar{e}'_1 | e'_2)$  has the second block of weight  $\text{wgt}(e'_2) \leq \text{wgt}(e_2) < d_{j-1}\delta$ , it satisfies  $C'_j(\bar{e}')^T = 0$ , and in its block representation (16) the remaining nonzero vectors  $f_\ell \in H(A_{j-1}, A'_j)$  have weights  $d_{j-1}$  or larger.

Step 3: For sure, there remains fewer than  $\delta$  of nonzero vectors  $f_\ell$ . Thus, in a decomposition,  $e'_2 = \sum_{j=1}^{n_{j-1}} z_j \otimes c_j$ , where  $z_j \in \mathbb{F}_2^{n_{j-1}}$  have the only nonzero bit at  $j$ , and  $c_j \in \mathbb{F}_2^c$ , the union of supports of the vectors  $c_j$ ,  $I_2$ , has size  $c' \equiv |I_2| < \delta$ . Indeed,  $I_2$  is just the set of the indices  $\ell$  corresponding to the remaining nonzero vectors  $f_\ell$ . Construct a matrix  $P' = P[I_2]$  by dropping the columns of  $P$  outside of  $I_2$ . Since there are fewer than  $\delta$  columns left,  $c' < \delta$ , the resulting classical code contains no nonzero vectors,  $c' = \text{rank } P'$ . Construct the modified matrices  $C''_j$  and  $C''_{j+1}$  and define the punctured vectors  $e''_2 = \sum_{j=1}^{n_0} z_j \otimes c_j[I_2]$  and  $e'' = (\bar{e}'_1 | e''_2)$  such that  $C''_j (e'')^T = 0$ . Now, after we trimmed the columns of both  $A_j$  and of  $P$ , according to Eq. (15), the homology group  $H(C''_j, C''_{j+1})$  is trivial. This implies that  $e''$  must be a linear combination of the columns of  $C''_{j+1}$ , that is,  $(e'')^T = C''_{j+1}\beta^T$ , for some binary vector  $\beta$ .

The transformation to  $C''_{j+1}$  and  $e''$  amounts to dropping some columns and rows from the matrix  $C'_{j+1}$ , and some matching positions from  $\bar{e}'$ . All nonzero bits of  $\bar{e}'$  are preserved, as are all involved columns of  $P$ . This implies that  $\bar{e}'$  can be also obtained as a linear combination of columns of  $C'_{j+1}$ . Combined with the equivalence transformation in step 2, we get  $(e')^T = C'_{j+1}(\alpha')^T$ ; the construction of step 1 then implies existence of  $\alpha \in C_{j+1}$  such

that  $e^T = C_{j+1}\alpha^T$  for the original two-block vector  $e = (e_1 | e_2)$ . Thus, any such  $e$  with block weights  $w_1 < d_j$  and  $w_2 < d_{j-1}\delta$  which satisfies  $C_j e^T = 0$  is necessarily a linear combination of the columns of  $C_{j+1}$ . This guarantees  $d'_j \geq \min(d_j, d_{j-1}\delta)$ .

To complete the proof, consider the case (ii). Here, step 1 can be omitted; the matrices resulting from steps 2 and 3 alone would give the trivial homology group, regardless of the weight  $\text{wgt}(e_1)$  of the first block. Thus, in this case we get the lower bound  $d'_j \geq d_{j-1}\delta$ .

Let us now consider tensor products of several 1-complexes. The space dimensions, row and column weights, and homology group distances do not depend on the order of the terms in the product. Further, if the matrices used to construct one-complexes are  $(v, \omega)$  sparse, that is, their column and row weights do not exceed  $v$  and  $\omega$ , respectively, the matrices in the resulting  $m$ -chain complex are  $(mv, m\omega)$  sparse. In particular, when  $\mathcal{K} = \mathcal{K}(R)$  is a 1-complex associated with a circulant check matrix  $R$  of the repetition code,  $\mathcal{K}^{\times D}$  recovers all the  $D$ -dimensional toric codes.

Next, consider an  $r \times c$  full-row rank binary matrix  $P$  with  $r < c$ , and assume that a binary code  $C_P^1$  has distance  $\delta$ . The 1-complex  $\mathcal{K} \equiv \mathcal{K}(P)$  has two nontrivial spaces of dimensions  $r$  and  $c$ ; the corresponding homology groups have ranks 0,  $\kappa$ , and distances  $\infty, \delta$ . The 1-complex  $\tilde{\mathcal{K}} \equiv \mathcal{K}(P^T)$  generated by the transposed matrix has equivalent spaces taken in the opposite order, with the same homology group ranks, but the distances are now 1 and  $\infty$ , respectively. For the  $(a+b)$ -complex  $\mathcal{K}^{(a,b)} \equiv \mathcal{K}^{\times a} \times \tilde{\mathcal{K}}^{\times b}$  constructed as tensor products of  $\mathcal{K}$  and/or  $\tilde{\mathcal{K}}$  in any order, the only nontrivial homology group  $H_a(\mathcal{K}^{(a,b)})$ , acting in the space of dimension

$$n_a(\mathcal{K}^{(a,b)}) = \sum_{i=0}^a c^{2i} r^{a+b-2i} \binom{a}{i} \binom{b}{i} < (r+c)^{a+b},$$

has rank  $\kappa^{a+b}$  and distance  $\delta^a$ . The corresponding quantum CSS code has distance  $\min(\delta^a, \delta^b)$ , and its stabilizer generators have weights not exceeding  $(a+b)\max(v, \omega)$ .

Good weight-limited classical codes with finite rates  $\kappa/c$  and finite relative distances  $\delta/c$  can be obtained from ensembles of large random matrices [4–7]. Any of these can be used in the present construction. Then, for any pair  $(a, b)$  of natural numbers, we can generate weight-limited q-LDPC codes with finite rates and the distances  $d_X = \delta^a$ ,  $d_Z = \delta^b$  whose product scales linearly with the code length. QHP codes are a special case of this construction with  $a = b = 1$ .

Unlike in the case of QHP codes, with any  $a > 1, b > 1$ , the rows of matrices  $G_X = K_a \equiv K_a(\mathcal{K}^{(a,b)})$ ,  $G_Z = K_{a+1}^T$  satisfy a large number of linear relations resulting from the orthogonality with the matrices  $K_{a-1}$  and  $K_{a+2}$ , respectively. These can be used to correct syndrome

measurement errors. Even though the resulting syndrome codes do not have large distances (with a finite probability some errors remain), the use of such codes in repeated measurement settings could simplify the decoding and/or improve the decoding success probability in the case of adversarial noise [34]. Such improvements with stochastic noise have been demonstrated numerically in the case of  $D = 4$  toric codes in Ref. [54].

In conclusion, we derived an explicit expression for the distances of the homology groups in a tensor product of two chain complexes assuming one of the complexes has length two. Immediate use of this result is in theory of quantum LDPC codes. Our result greatly extends the family of QHP codes whose parameters are known explicitly. Higher-dimensional QHP codes can be especially useful in fault-tolerant quantum computation, to optimize repeated syndrome measurement in the presence of measurement errors.

In addition, we believe that the lower distance bound in Theorem 1 can be extended to a general product of two chain complexes. If this is the case, the right-hand side in Eq. (11) would give explicitly the distances, not just an upper bound. Such a result could have substantial applications in many areas of science where homology is used.

L. P. P. is grateful to Jean-Pierre Tillich for illuminating discussions, and to the Institute Henri Poincaré for hospitality. This research was supported in part by the NSF Division of Physics via Grants No. 1416578 and No. 1820939.

---

\*wzeng002@ucr.edu

†leonid.pryadko@ucr.edu

- [1] A. A. Kovalev and L. P. Pryadko, Fault tolerance of quantum low-density parity check codes with sublinear distance scaling, *Phys. Rev. A* **87**, 020304(R) (2013).
- [2] I. Dumer, A. A. Kovalev, and L. P. Pryadko, Thresholds for Correcting Errors, Erasures, and Faulty Syndrome Measurements in Degenerate Quantum Codes, *Phys. Rev. Lett.* **115**, 050502 (2015).
- [3] D. Gottesman, Fault-tolerant quantum computation with constant overhead, *Quantum Inf. Comput.* **14**, 1338 (2014).
- [4] R. Gallager, Low-density parity-check codes, *IRE Trans. Inf. Theory* **8**, 21 (1962).
- [5] R. G. Gallager, *Low-Density Parity-Check Codes* (MIT Press, Cambridge, MA, 1963).
- [6] S. Litsyn and V. Shevelev, On ensembles of low-density parity-check codes: Asymptotic distance distributions, *IEEE Trans. Inf. Theory* **48**, 887 (2002).
- [7] T. J. Richardson, M. A. Shokrollahi, and R. L. Urbanke, Design of capacity-approaching irregular low-density parity-check codes, *IEEE Trans. Inf. Theory* **47**, 619 (2001).
- [8] G. Zémor, On Cayley graphs, surface codes, and the limits of homological coding for quantum error correction, in *Proceedings of the Coding and Cryptology: Second International Workshop, IWCC 2009*, edited by Y. M. Chee, C. Li, S. Ling, H. Wang, and C. Xing (Springer, Berlin, Heidelberg, 2009), pp. 259–273.
- [9] N. Delfosse and G. Zémor, Quantum erasure-correcting codes and percolation on regular tilings of the hyperbolic plane, in *Information Theory Workshop (ITW), 2010* (IEEE, New York, 2010), pp. 1–5.
- [10] N. P. Breuckmann and B. M. Terhal, Constructions and noise threshold of hyperbolic surface codes, *IEEE Trans. Inf. Theory* **62**, 3731 (2016).
- [11] N. P. Breuckmann, C. Vuillot, E. Campbell, A. Krishna, and B. M. Terhal, Hyperbolic and semi-hyperbolic surface codes for quantum storage, *Quantum Sci. Technol.* **2**, 035007 (2017).
- [12] L. Guth and A. Lubotzky, Quantum error correcting codes and 4-dimensional arithmetic hyperbolic manifolds, *J. Math. Phys. (N.Y.)* **55**, 082202 (2014).
- [13] J.-P. Tillich and G. Zémor, Quantum LDPC codes with positive rate and minimum distance proportional to  $\sqrt{n}$ , in *Proceedings of the IEEE International Symposium on Information Theory (ISIT)* (IEEE, New York, 2009), pp. 799–803.
- [14] J.-P. Tillich and G. Zémor, Quantum LDPC codes with positive rate and minimum distance proportional to the square root of the blocklength, *IEEE Trans. Inf. Theory* **60**, 1193 (2014).
- [15] A. A. Kovalev and L. P. Pryadko, Quantum Kronecker sum-product low-density parity-check codes with finite rate, *Phys. Rev. A* **88**, 012311 (2013).
- [16] A. Couvreur, N. Delfosse, and G. Zémor, A construction of quantum LDPC codes from Cayley graphs, *IEEE Trans. Inf. Theory* **59**, 6087 (2013).
- [17] S. Bravyi and M. B. Hastings, Homological product codes, [arXiv:1311.0885](https://arxiv.org/abs/1311.0885).
- [18] B. Audoux, An application of Khovanov homology to quantum codes, *Ann. Inst. Henri Poincaré* **1**, 185223 (2014).
- [19] B. Audoux and A. Couvreur, On tensor products of CSS codes, [arXiv:1512.07081](https://arxiv.org/abs/1512.07081).
- [20] M. B. Hastings, Quantum codes from high-dimensional manifolds, [arXiv:1608.05089](https://arxiv.org/abs/1608.05089).
- [21] M. B. Hastings, Weight reduction for quantum codes, [arXiv:1611.03790](https://arxiv.org/abs/1611.03790).
- [22] S. B. Bravyi and A. Yu. Kitaev, Quantum codes on a lattice with boundary, [arXiv:quant-ph/9811052](https://arxiv.org/abs/quant-ph/9811052).
- [23] M. H. Freedman and D. A. Meyer, Projective plane and planar quantum codes, *Found. Comput. Math.* **1**, 325332 (2001).
- [24] E. Dennis, A. Kitaev, A. Landahl, and J. Preskill, Topological quantum memory, *J. Math. Phys. (N.Y.)* **43**, 4452 (2002).
- [25] H. Bombin and M. A. Martin-Delgado, Homological error correction: Classical and quantum codes, *J. Math. Phys. (N.Y.)* **48**, 052105 (2007).
- [26] C. Castelnovo and C. Chamon, Topological order in a three-dimensional toric code at finite temperature, *Phys. Rev. B* **78**, 155120 (2008).
- [27] D. Mazáč and A. Hamma, Topological order, entanglement, and quantum memory at finite temperature, *Ann. Phys. (Amsterdam)* **327**, 2096 (2012).

- [28] H. Bombin, R. W. Chhajlany, M. Horodecki, and M. A. Martin-Delgado, Self-correcting quantum computers, *New J. Phys.* **15**, 055023 (2013).
- [29] A. Yu. Kitaev, Fault-tolerant quantum computation by anyons, *Ann. Phys. (Amsterdam)* **303**, 2 (2003).
- [30] S. Bravyi and B. Terhal, A no-go theorem for a two-dimensional self-correcting quantum memory based on stabilizer codes, *New J. Phys.* **11**, 043029 (2009).
- [31] S. Bravyi, D. Poulin, and B. Terhal, Tradeoffs for Reliable Quantum Information Storage in 2D Systems, *Phys. Rev. Lett.* **104**, 050503 (2010).
- [32] N. Delfosse, Tradeoffs for reliable quantum information storage in surface codes and color codes, in *Proceedings of the IEEE International Symposium on Information Theory (ISIT), 2013* (IEEE, New York, 2013), pp. 917–921.
- [33] S. T. Flammia, J. Haah, M. J. Kastoryano, and I. H. Kim, Limits on the storage of quantum information in a volume of space, *Quantum* **1**, 4 (2017).
- [34] E. T. Campbell, A theory of single-shot error correction for adversarial noise, *Quantum Sci. Technol.* **4**, 025006 (2019).
- [35] C. Wang, J. Harrington, and J. Preskill, Confinement-Higgs transition in a disordered gauge theory and the accuracy threshold for quantum memory, *Ann. Phys. (Amsterdam)* **303**, 31 (2003).
- [36] R. S. Andrist, Understanding topological quantum error-correction codes using classical spin models, Ph.D. thesis, Department of Physics, ETH Zürich, 2012.
- [37] Y. Fujiwara, Ability of stabilizer quantum error correction to protect itself from its own imperfection, *Phys. Rev. A* **90**, 062304 (2014).
- [38] A. Ashikhmin, C. Y. Lai, and T. A. Brun, Robust quantum error syndrome extraction by classical coding, in *2014 IEEE International Symposium on Information Theory* (IEEE, New York, 2014), pp. 546–550.
- [39] A. Ashikhmin, C. Y. Lai, and T. A. Brun, Correction of data and syndrome errors by stabilizer codes, in *2016 IEEE International Symposium on Information Theory (ISIT)* (IEEE, New York, 2016), pp. 2274–2278.
- [40] L. Ioffe and M. Mézard, Asymmetric quantum error-correcting codes, *Phys. Rev. A* **75**, 032345 (2007).
- [41] Z. W. E. Evans, A. M. Stephens, J. H. Cole, and L. C. L. Hollenberg, Error correction optimisation in the presence of  $x/z$  asymmetry, [arXiv:0709.3875](https://arxiv.org/abs/0709.3875).
- [42] A. M. Stephens, Z. W. E. Evans, S. J. Devitt, and L. C. L. Hollenberg, Asymmetric quantum error correction via code conversion, *Phys. Rev. A* **77**, 062335 (2008).
- [43] P. Aliferis and J. Preskill, Fault-tolerant quantum computation against biased noise, *Phys. Rev. A* **78**, 052331 (2008).
- [44] P. K. Sarvepalli, A. Klappenecker, and M. Rötteler, Asymmetric quantum codes: Constructions, bounds and performance, *Proc. R. Soc. A* **465**, 1645 (2009).
- [45] D. K. Tuckett, S. D. Bartlett, and S. T. Flammia, Ultrahigh Error Threshold for Surface Codes with Biased Noise, *Phys. Rev. Lett.* **120**, 050505 (2018).
- [46] C. A. Weibel, *An Introduction to Homological Algebra*, Cambridge Studies in Advanced Mathematics Vol. 38 (Cambridge University Press, Cambridge, England, 1994).
- [47] F. J. MacWilliams and N. J. A. Sloane, *The Theory of Error-Correcting Codes* (North-Holland, Amsterdam, 1981).
- [48] D. Gottesman, Stabilizer codes and quantum error correction, Ph.D. thesis, Caltech, Pasadena, 1997.
- [49] M. A. Nielsen and I. L. Chuang, *Quantum Computation and Quantum Information* (Cambridge University Press, Cambridge, England, 2000).
- [50] A. R. Calderbank, E. M. Rains, P. M. Shor, and N. J. A. Sloane, Quantum error correction via codes over  $GF(4)$ , *IEEE Trans. Inf. Theory* **44**, 1369 (1998).
- [51] A. R. Calderbank and P. W. Shor, Good quantum error-correcting codes exist, *Phys. Rev. A* **54**, 1098 (1996).
- [52] A. M. Steane, Simple quantum error-correcting codes, *Phys. Rev. A* **54**, 4741 (1996).
- [53] See Supplemental Material at <http://link.aps.org/supplemental/10.1103/PhysRevLett.122.230501> for a more detailed version of the proof.
- [54] N. P. Breuckmann, K. Duivenvoorden, D. Michels, and B. M. Terhal, Local decoders for the 2D and 4D toric code, *Quantum Inf. Comput.* **17**, 0181 (2017).