Mean Inner Potential of Liquid Water

Murat Nulati Yesibolati¹, Simone Laganà, Hongyu Sun¹, Marco Beleggia¹, Shawn M. Kathmann,^{2,*}

Takeshi Kasama,^{1,†} and Kristian Mølhave^{1,‡}

¹DTU Nanolab, National Centre for Nano Fabrication and Characterization, Technical University of Denmark,

Building 307, 2800 Kgs. Lyngby, Denmark

²Physical Sciences Division, Pacific Northwest National Laboratory, 902 Battelle Boulevard,

P.O. Box 999, Richland, Washington 99352, USA

 (Received 29 September 2019; revised manuscript received 20 November 2019; accepted 23 December 2019; published 13 February 2020)

Improving our experimental and theoretical knowledge of electric potentials at liquid-solid boundaries is essential to achieve a deeper understanding of the driving forces behind interfacial processes. Electron holography has proved successful in probing solid-solid interfaces but requires knowledge of the materials' mean inner potential (MIP, V_0), which is a fundamental bulk material property. Combining off-axis electron holography with liquid phase transmission electron microscopy (LPTEM), we provide the first quantitative MIP determination of liquid water $V_0 = +4.48 \pm 0.19$ V. This value is larger than most theoretical predictions, and to explain the disagreement we assess the dominant factors needed in quantum simulations of liquid water. A precise MIP lays the foundations for nanoscale holographic potential measurements in liquids, and provides a benchmark to improve quantum mechanical descriptions of aqueous systems and their interfaces in, e.g., electrochemistry, solvation processes, and spectroscopy.

DOI: 10.1103/PhysRevLett.124.065502

Introduction.—The mean inner potential (MIP, V_0) is the volume-averaged electrostatic potential of a material with respect to a distant vacuum reference region at zero volts. The MIP is an intrinsic material property that depends on its elemental composition, structure, and electronic configuration [1]. The MIP is also known as the Bethe potential since Hans Bethe was the first to derive it [2], and provides an essential benchmark for both classical [3] and quantum mechanical (OM) molecular modeling [4], especially when studying electrodynamics of materials. For liquid water in particular, acquiring a reliable experimental MIP will benefit the accurate quantification of a variety of processes, e.g., for theoretical prediction and data interpretation of photoelectron spectroscopy (PES) [5,6], and will shed light on the nature of surface potentials, which is a source of debate in various scientific communities [7]. Using the MIP as a benchmark will also lead to improvements in models of aqueous systems where electrical potentials or fields at interfaces influence ion solvation processes [3], Stark vibrational spectroscopy [8], and electrocatalysis [9], where QM models preferably should be able to predict a reliable MIP before being used. Hence, rigorous MIP measurements and theoretical representations are essential to improve our understanding of water's electric properties and thereby our capabilities to predict and rationally design processes involving aqueous systems.

The MIP can also be characterized as an electric potential jump [3] experienced by an electron when crossing the surface from vacuum to the bulk material. It can be influenced by the material's surface termination, which in the past may have caused some discrepancies [10]. For a well-defined surface and bulk structure, the MIP is also experimentally and quantum mechanically well-defined.

In the simplest quantum approximation, called the independent atom model (IAM), isolated atoms in vacuum are superimposed at the relevant density to estimate an upper bound of the MIP (V_0) using Dirac-Fock electron scattering factors $f_i^e(0)$ at zero angle for the *i* atoms in a unit cell of volume Ω [11–13]

$$V_0^{\text{IAM}} = \frac{(h^2/2\pi m_e e)}{\Omega} \sum f_i^e(0). \tag{1}$$

For liquid water at 25 °C, $V_0^{\text{water,IAM}} = +4.87 \text{ V}$ [3,14,15]. Current x ray and electron diffraction measurements rely on the IAM to obtain atomic electron densities and potentials, respectively [4,15,16], however, a more accurate MIP would be a significant improvement.

In QM density functional theory (DFT), the MIP can be calculated by either averaging the total electric potential from an all-electron simulation, or by summing the contribution of the surface dipole layer and bulk quadrupole contributions [12,17] using maximally localized Wannier centers [18]. Table I summarizes published experimental and theoretical water MIP values, and also density corrected values [3,4,18–22], as the MIP is proportional to mass density via the unit cell volume Ω [23,24]. The quantum MIP values for vitreous ice and water vary significantly around +3.72 V (as corrected via the liquid

PHYSICAL REVIEW LETTERS 124 , 065502 (2020))
---	----

TABLE I.	Theoretical	and	experimental	MIP	values

<i>V</i> ₀ [V]	Method	V_0 [V] @ 1 g/cm ³
<4.87	IAM	<4.49
3.63	DFT [18]	3.94
3.1 ± 0.2	DFT [3]	3.87
3.8 ± 0.2	DFT ^[4]	3.8
~3.70	DFT [20]	~3.4
4.32	DFT [19]	4.32
3.5 ± 1.2	TEM [21]	3.72
3.5 ± 0.5	TEM [22]	3.5

density), the only previously reported experimental MIP value based on vitrified ice [21]. Some DFT models employ nuclear core corrections [4,19], where the true nuclear Z/r potential, from the nuclear delta function of charge Z, is used in the actual MIP calculation, rather than the very narrow Gaussian nuclei used for numerical purposes. Thus, an accurate measurement of the MIP of liquid water provides an essential guiding benchmark for improving quantum descriptions of water.

Off-axis electron holography in a transmission electron microscope (TEM) is one of the most accurate methods to measure the MIP as well as mapping out the electric potentials through materials and their interfaces [25]. However, liquids have not been measured reliably, due to evaporation in the TEM vacuum, charging, and radiation damage [26,27], as well as a lack of accurate thickness measurements when using chip-based liquid phase TEM (LPTEM) [28]. To date, the only water MIP $V_0^{\text{ice}} = +3.5 \pm$ 1.2 V [21] was measured on an amorphous vitrified ice sample at cryogenic temperature, by measuring the electron wave phase shift through polystyrene spheres with a known MIP relative to that of the surrounding vitrified ice. This value could include systematic errors from charging, thermal expansion [23,24] of both materials, and recrystallization. Recently, an estimated thickness of a single water droplet in LPTEM gave $V_0^{\text{water}} = +3.5 \pm 0.5 \text{ V}$ [22].

We present the first quantitative experimental liquid water MIP measurements by developing a novel LPTEM nanochannel liquid cell system [29] [Fig. 1(a), and Supplemental Material S1 [30]] and using electron holography to measure the phase change of the electron wave after passing through liquid water of known thickness (Supplemental Material S2 [30]). Assuming unbiased nonmagnetic materials, the electron wave phase shift ($\Delta \varphi$), relative to a reference wave passing through vacuum, is proportional to liquid thickness *t* and MIP, V₀ as [25]

$$\Delta \varphi = C_E V_0 t, \qquad C_E = \frac{2\pi}{\lambda} \frac{E + E_0}{E(E + 2E_0)}. \tag{2}$$

 C_E is a constant that depends on the TEM beam energy (*E*). λ is the relativistic electron wavelength and $E_0 = 511$ keV is the rest mass energy of the electron. At 300 kV, $C_E = 6.53 \times 10^6$ rad/(Vm) [45]. The holographic interference



FIG. 1. Thickness based MIP measurement. (a) Illustration of the setup for nanochannel LPTEM off-axis electron holography. Interference of object and reference waves create the interference hologram in (b) of water near a nanochannel sidewall, with a stable meniscus to a bubble in the channel. (c) Reconstructed phase image with color code of $\Delta \varphi$ in radian. (d) Schematic nanochannel cross section with liquid thickness *t*. (e) Phase profile along the *x* direction from the white box in (c); $\Delta \varphi$ was averaged over 80 nm in the *y* direction. (f) Liquid water $\Delta \phi$ from three channels with liquid thickness *t*, and linear fit $\Delta \varphi = C_E V_0^{\text{water},t} t + a$.

image in Fig. 1(b) is of a nanochannel filled with liquid water and a stable radiolytic gas bubble. Holographic image reconstruction provides the phase image as in Fig. 1(c).

As shown in Figs. 1(c) and 1(e), Si_3N_4 has larger MIP than water, therefore, the Si_3N_4 sidewall gives a larger phase shift. The water MIP is measured from the phase profile plateau relative to outside the channel, Fig. 1(e). The holographic analysis, assumptions, and QM simulations are further described in Supplemental Material S3-S4 [30]. Electron beam current and charging influence were found to be negligible, as detailed in Supplemental Material S5 and S6 [30].

Three nanochannel liquid cells were used with different liquid layer thicknesses t, independently verified by chip cross-section images taken by scanning electron microscopy (Supplemental Material S7 [30]). The correlation between liquid thickness and phase change is shown in Fig. 1(f) with each data point representing different regions of a given chip and a linear fit as Eq. (1), $\Delta \varphi = C_E V_0^{\text{water},t} t + a$, including uncertainty from both phase and thickness. A fitted parameter $a = 0.38 \pm 0.15$ rad was included to account for minor local variations in charging and thickness, as well as possible deviations from linearity for very thin layers [46]. The *a* parameter is close to zero within the overall error bars, and for a thickness based MIP measurement $V_0^{\text{water},t} = +4.48 \pm 0.19V$.

A second analysis was done, using the inelastic mean free path of electrons (λ_{IMFP}), based on the correlation between the phase and amplitude variation [47] in the meniscus with varying water layer thickness. Interference fringe formation [25] is based on coherent electrons and the holographic image analysis removes any inelastic electron scattering contribution. The reconstructed amplitude image is equivalent to a zero loss energy filtered image [47,48] related to λ_{IMFP} as

$$\frac{t}{\lambda_{\rm IMFP}} = -2 \times \ln \frac{A_{\rm obj}}{A_{\rm ref}}.$$
(3)

Combined with Eq. (2), a MIP, V_0^{λ} can be found without knowing the sample thickness

$$\frac{\Delta\varphi}{-2C_E \ln\frac{A_{\rm obj}}{A_{\rm ref}}} = V_0^{\lambda} \lambda_{\rm IMFP},\tag{4}$$

An example of the correlation between phase and amplitude in the meniscus is shown in Figs. 2(a)–2(c) and more in the Supplemental Material S8 [30], with a linear fit as expected from Eq. (4) of the phase shift, $\Delta \varphi$, versus $-\ln(A_{obj}/A_{ref})$, where amplitude in the meniscus A_{obj} is normalized relative to the bubble region without liquid A_{ref} . This relies on knowing the holographic λ_{IMFP} with high precision which is expected to be shorter than that determined by electron energy loss spectrometry (EELS) TEM [49–52], as EELS cannot resolve the small losses that reduce coherence in holography. Here λ_{IMFP} is based on the part of the channel with known liquid layer thickness using Eq. (3) as detailed in the Supplemental Material S8 [30], giving a holographic $\lambda_{IMFP} = 164 \pm 40$ nm, as expected smaller than published EELS based water λ_{IMFP} [53].

The linear fit as in Fig. 2(c) is only done in the thickness varying meniscus, and passes, within uncertainty, close to the origin, where the slight offset could be due to minor membrane thickness variations, or residual liquid or humid layers and vapor in the assumed empty bubble region,



FIG. 2. Example of $\lambda_{\rm IMFP}$ based water MIP measurement. (a) Phase image and corresponding profile plots near a meniscus; (b) the inverse logarithm of amplitude $(A_{\rm obj})$ normalized to region without liquid $(A_{\rm ref})$, and corresponding profile plots. (c) Plot of correlation and linear fit to $-\ln(A_{\rm obj}/A_{\rm ref})$ vs $\Delta \varphi$. The scale bar is 50 nm.

which is another reason for including the *a* parameter in Fig. 1(f). The λ_{IMFP} based MIP is $V_0^{\text{water},\lambda} = +4.3 \pm 0.8 \text{ V}$ from averaging the slopes, agreeing well with the thickness based MIP (Fig. 2). With larger uncertainty and implicit λ_{IMFP} reliance on thickness, the λ_{IMFP} based MIP is considered a self-consistency check confirming $V_0^{\text{water},t}$.

As shown in Fig. 3, the liquid water MIP values are larger than both the earlier measurement of vitrified ice [21] and the droplet estimated value [22], but partly within their upper uncertainty range. The vitrified ice result increases slightly when density scaled from 0.94 to 1 g/cm³ [23], and could be influenced by the degree of vitrification [24].

We consider the QM simulations of flexible water molecules (QMF) by Remsing *et al.* [19]. The QMF give a bulk quadrupole contribution $V_0^{\text{water,QMF,bulk}} = 3.84$ V, 0.08 V higher than the rigid model [4], indicating a negligible effect from flexibility. The QMF surface dipole contribution is $V_0^{\text{water,QMF,surf}} = +0.48$ V, which when added to $V_0^{\text{water,QMF,bulk}}$ gives $V_0^{\text{water,QMF}} = +4.32 \pm$ 0.20 V as the best matching theoretical MIP from Table I, and is in excellent agreement with our measurements. The main difference between the QMF and the others listed in Table I is a combination of using the correct density, nuclear core correction that adds ca. +0.4 V, and the surface dipole addition. Importantly, the quantum and experimental MIPs are only about -0.5 V below the IAM upper limit MIP. This means that the total electronic redistribution (making OH bonds, lone pairs, and hydrogen bonding) in going from the IAM model to liquid water molecules only amounts to a MIP decrease of -0.5 V. We note that our MIP value is also in excellent agreement with water's diamagnetic susceptibility (Supplemental Material S9 [30]).

As noted, a reliable water MIP is important when comparing condensed bulk phase QM PES calculations with measurement, where the measured spectra are with respect to a vacuum at zero volts, similar to the reference potential for the holographic MIP. Using the MIP, all of the computed electronic energy levels must be corrected to the vacuum reference level [6]. In particular, the MIP of +4.48 V makes a large contribution to computed PES by shifting the electronic band offsets by more than 45% of the threshold ionization energy (~9.9 eV). Currently QM values around +3.7 V are used [20] to predict photoelectron ionization thresholds [5,6]. Beyond PES, solvation processes [3], and field-induced processes such as Stark vibrational spectroscopy [8] and electrocatalysis [9] would likely benefit from reliable MIPs to benchmark condensed phase electric potentials before calculating the fields underlving such processes.

In summary, we presented the first quantitative MIP measurement of liquid water at $V_0^{\text{water},t} = +4.48 \pm 0.19 \text{ V},$ by combining off-axis electron holography with a nanochannel liquid phase TEM system, giving direct proportionality between the transmitted electron wave phase shift and liquid thickness. A self-consistency check was made with a method based on the inelastic mean free path of electrons. Both methods' MIPs are in excellent agreement and within error bars of the best available condensed phase quantum mechanical simulation including the correct liquid density, surface dipole potential, and nuclear core corrections. The values are below the IAM limit and within the upper uncertainty of vitrified ice measurements [21]. These measurements provide critical benchmarks for quantum mechanical simulations of electric potentials inside water and at its interfaces to matter. This novel MIP technique is fundamental to future electron holographic microscopy of electric potentials in nanoscale liquid processes.

All data needed to draw these conclusions are presented in the Letter and Supplemental Material [30].

This paper the authors acknowledge core facilities support from DTU Nanolab and DTU Health tech, and engineering support from Per Thor Jonassen, Wilhelmus Huyzer, and Adam Fuller. The authors acknowledge helpful discussions with Nestor J. Zaluzec, Dwayne Miller, Tim Duigan, Marcel Baer, Chris Mundy, Gregory Schenter, Mohammad Koleini and Mads Brandbyge. Funding: The research was supported by Technical University of Denmark and from the Danish Research Council for Technology and Production Case No. 12-126194. S. M. K. was supported by the U.S. Department of Energy, Office



FIG. 3. Comparison of water MIP values. From the nanochannel thickness based method, $V_0^{water,t}$; λ_{IMFP} based method, $V_0^{water,\lambda}$; the QMF model, $V_0^{water,QMF}$ [19]; measurements on vitrified ice, V_0^{ice} [21], also scaled to liquid density (*); and the water droplet estimate, V_0^{water} [22]. Red-solid line is the upper limit $V_0^{water,IAM}$.

of Science, Office of Basic Energy Sciences, Division of Chemical Sciences, Geosciences & Biosciences. PNNL is operated by Battelle for the U.S. Department of Energy under Contract No. DE-AC05-76RL01830. This research used resources of the National Energy Research Scientific Computing Center, which is supported by the Office of Science of the U.S. Department of Energy under Contract No. DE-AC02-05CH11231. This work was supported in part by the Advanced Materials for Energy-Water Systems (AMEWS) Center, an Energy Frontier Research Center funded by the U.S. Department of Energy, Office of Science, Basic Energy Sciences. K.M. and M.N.Y. proposed and directed the research with help from S.L., T. K., S. M. K., M. B., H. Y. S. Chips were fabricated by S. L., and M. N. Y. engineered the custom-made TEM holder; M. N. Y. and T. K. carried out experiments and data analysis; S. M. K. implemented simulation; M. B. helped in charge analysis; H. Y. S. helped in experiment both in chip preparation and TEM operation. M. N. Y., K. M. and S. M. K. wrote the manuscript; all authors contributed to the discussion of the experimental results and revision of the text.

*Corresponding author. Shawn.Kathmann@pnnl.gov †Deceased. *Corresponding author. krmo@dtu.dk

- [1] J. C. H. Spence, Acta Crystallogr. Sect. A 49, 231 (1993).
- [2] H. Bethe, Ann. Phys. (Berlin) **392**, 55 (1928).
- [3] S. M. Kathmann, I. F. W. Kuo, C. J. Mundy, and G. K. Schenter, J. Phys. Chem. B 115, 4369 (2011).

- [4] B. Sellner and S. M. Kathmann, J. Chem. Phys. 141, 18C534 (2014).
- [5] G. Olivieri, K. M. Parry, C. J. Powell, D. J. Tobias, and M. A. Brown, J. Chem. Phys. 144, 154704 (2016).
- [6] A. P. Gaiduk, M. Govoni, R. Seidel, J. H. Skone, B. Winter, and G. Galli, J. Am. Chem. Soc. 138, 6912 (2016).
- [7] T. S. Hofer and P. H. Hünenberger, J. Chem. Phys. 148, 222814 (2018).
- [8] S. M. Gruenbaum, C. J. Tainter, L. Shi, Y. Ni, and J. L. Skinner, J. Chem. Theory Comput. 9, 3109 (2013).
- [9] M. Liu et al., Nature (London) 537, 382 (2016).
- [10] R. S. Pennington, C. B. Boothroyd, and R. E. Dunin-Borkowski, Ultramicroscopy 159, 34 (2015).
- [11] J. M. Cowley, in *Diffraction Physics*, edited by J. M. Cowley (North-Holland, Amsterdam, 1995), 3rd ed., p. 77.
- [12] M. Gajdardziska-Josifovska and A. H. Carim, in *Introduction to Electron Holography*, edited by E. Völkl, L. F. Allard, and D. C. Joy (Springer US, Boston, MA, 1999), p. 267.
- [13] A. Sanchez and M. A. Ochando, J. Phys. C 18, 33 (1985).
- [14] D. Rez, P. Rez, and I. Grant, Acta Crystallogr. Sect. A 50, 481 (1994).
- [15] L. M. Peng, Micron 30, 625 (1999).
- [16] J. M. Sorenson, G. Hura, R. M. Glaeser, and T. Head-Gordon, J. Chem. Phys. **113**, 9149 (2000).
- [17] P. Becker and P. Coppens, Acta Crystallogr. Sect. A 46, 254 (1990).
- [18] K. Leung, J. Phys. Chem. Lett. 1, 496 (2010).
- [19] R. C. Remsing, M. D. Baer, G. K. Schenter, C. J. Mundy, and J. D. Weeks, J. Phys. Chem. Lett. 5, 2767 (2014).
- [20] T. A. Pham, C. Zhang, E. Schwegler, and G. Galli, Phys. Rev. B 89, 060202(R) (2014).
- [21] A. Harsher and H. Lichte, Inelastic mean free path and mean inner potential of carbon foil and vitrified ice measured with electron holography, Electron Microscopy General Interest and Instrumentation, Vol. 1 (IOP Publishing Ltd, Bristol, 1998).
- [22] T. Prozorov, T. P. Almeida, A. Kovács, and R. E. Dunin-Borkowski, J. R. Soc. Interface 14, 20170464 (2017).
- [23] J. A. Ghormley and C. J. Hochanadel, Science 171, 62 (1971).
- [24] Y. Huang, X. Zhang, Z. Ma, W. Li, Y. Zhou, J. Zhou, W. Zheng, and C. Q. Sun, Sci. Rep. 3, 3005 (2013).
- [25] E. Völkl, L.F. Allard, and D.C. Joy, *Introduction to Electron Holography* (Kluwer Academic/Plenum Publishers, New York, 1999).
- [26] M. Shirai, T. Tanigaki, S. Aizawa, H. S. Park, T. Matsuda, and D. Shindo, Ultramicroscopy 146, 125 (2014).
- [27] N. M. Schneider, M. M. Norton, B. J. Mendel, J. M. Grogan, F. M. Ross, and H. H. Bau, J. Phys. Chem. C 118, 22373 (2014).
- [28] F. M. Ross, Science 350 (2015).
- [29] S. Lagana, E. K. Mikkelsen, H. Sun, R. Marie, and K. Mølhave, *The 16th European Microscopy Congress 2016*, Lyon France, 5763 (2016).

- [30] See Supplemental Material at http://link.aps.org/ supplemental/10.1103/PhysRevLett.124.065502 for materials and methods (S1–S4), electron beam and charge influences (S5–S6), sample thickness measurement (S7), electron mean free path measurement (S8), and discussion of diamagnetic susceptibility (S9), which includes Refs. [31–44].
- [31] S. Laganá, E. K. Mikkelsen, R. Marie, O. Hansen, and K. Mølhave, Microelectron. Eng. 176, 71 (2017).
- [32] P. A. Midgley, Micron 32, 167 (2001).
- [33] D. K. Saldin and J. C. H. Spence, Ultramicroscopy 55, 397 (1994).
- [34] J. E. Hirsch, Ann. Phys. (Berlin) 526, 63 (2014).
- [35] M. Beleggia, L.C. Gontard, and R.E. Dunin-Borkowski, J. Phys. D 49, 294003 (2016).
- [36] M. Beleggia, T. Kasama, R. E. Dunin-Borkowski, S. Hofmann, and G. Pozzi, Appl. Phys. Lett. 98, 243101 (2011).
- [37] C. Gatel, A. Lubk, G. Pozzi, E. Snoeck, and M. Hÿtch, Phys. Rev. Lett. 111, 025501 (2013).
- [38] S. Bhattacharyya and C. T. Koch, and U. M. Hle, J. Ceram. Soc. Jpn. 114, 1005 (2006).
- [39] T. Malis, S. C. Cheng, and R. F. Egerton, J. Electron Microsc. Tech. 8, 193 (1988).
- [40] R. F. Egerton and S. C. Cheng, Ultramicroscopy 21, 231 (1987).
- [41] D. R. G. Mitchell, J. Microsc. 224, 187 (2006).
- [42] L. Rosenfeld, Naturwissenschaften 17, 49 (1929).
- [43] R. R. Lunt, S. Kena-Cohen, J. B. Benziger, and S. R. Forrest, Phys. Rev. Lett. 102, 065504 (2009).
- [44] Physical Constants of Organic Compounds, Magnetic Susceptibility of Inorganic Materials, Internet Version, CRC Handbook of Chemistry and Physics, 100 ed. (CRC Press, Taylor & Francis Group, 2019).
- [45] T. Kasama, R. E. Dunin-Borkowski, and M. Beleggia, in *Electron Holography of Magnetic Materials*, edited by F. A. M. Ramirez (intechopen, intechopen, 2011).
- [46] M. Wanner, D. Bach, D. Gerthsen, R. Werner, and B. Tesche, Ultramicroscopy 106, 341 (2006).
- [47] M. Gajdardziskajosifovska and M. R. Mccartney, Ultramicroscopy 53, 291 (1994).
- [48] M. R. McCartney and M. Gajdardziska-Josifovska, Ultramicroscopy 53, 283 (1994).
- [49] Z. Gan, M. DiNezza, Y.-H. Zhang, D. J. Smith, and M. R. McCartney, Microsc. Microanal. 21, 1406 (2015).
- [50] C. Cassidy, A. Dhar, and T. Shintake, Appl. Phys. Lett. 110, 163503 (2017).
- [51] F. Kern, D. Wolf, P. Pschera, and A. Lubk, Ultramicroscopy 171, 26 (2016).
- [52] A. Lubk, D. Wolf, and H. Lichte, Ultramicroscopy **110**, 438 (2010).
- [53] M. Tanase, J. Winterstein, R. Sharma, V. Aksyuk, G. Holland, and J. A. Liddle, Microsc. Microanal. 21, 1629 (2015).